

# MAPEI products for installing gauged porcelain tile panels (GPT)

Surface prep • Mortars • Grouts • Adhesive

# Surface prep *Planitop 330 Fast | Ultraplan Easy | Mapecem Quickpatch*



## Planitop® 330 Fast

Flattening walls is fast and easy with this fiber-reinforced wall render and vertical patch.

- For interior/exterior walls and floors
- 1/8" to 1-1/4" (3 mm to 3.2 cm) in thickness in a single coat
- Fast drying allows tile installation in 90 minutes with no shrinking.

	Product Code	Packaging
U.S. / Canada	2235823	Bag: 50 lbs. (22.7 kg)



## Ultraplan® Easy

It's rare to find a floor that meets the GPT flatness requirement of 1/8" (3 mm) variation within 10 feet (3.05 m). *Ultraplan Easy* lets you simply clean, prime and pour, and you're ready to tile in 3 to 4 hours.

- Interior, quick-setting self-leveling underlayment
- Featheredge to 2" (5 cm) in thickness
- High-strength; can withstand light foot traffic in 2 to 3 hours after installation

	Product Code	Packaging
U.S.	7492723	Bag: 50 lbs. (22.7 kg)



## Mapecem® Quickpatch **CO<sub>2</sub> FULLY OFFSET IN THE ENTIRE LIFE CYCLE\***

For smaller repairs or troweling, *Mapecem Quickpatch* provides a moisture-resistant solution.

- For interior/exterior concrete surfaces
- 1/16" to 3" (1.5 mm to 7.5 cm) in thickness
- Sets fast for easy and cost-efficient patching

	Product Code	Packaging
U.S./Canada	1190205	Bag: 10 lbs. (4.54 kg)
	1190211	Bag: 25 lbs. (11.3 kg)
U.S.	1190223	Bag: 50 lbs. (22.7 kg)



\* This highlighted product is part of the "CO<sub>2</sub> Fully Offset in the Entire Life Cycle" line of products. CO<sub>2</sub> emissions measured throughout the life cycle of products from the Zero line in 2023, using Life Cycle Assessment (LCA) methodology, verified and certified with EPDs, have been offset through the acquisition of third-party-certified carbon credits in support of renewable energy and forestry protection projects: A commitment to the planet, to people and to biodiversity. For more details on how emissions are calculated and on climate-mitigation projects that are financed through certified carbon credits, visit [www.mapei.com/us/sustainable-products](http://www.mapei.com/us/sustainable-products).





## MAPEI Ultralite® S2


Combining lightweight technology with a lower water ratio for faster curing, MAPEI Ultralite S2 is a smart choice.

- Lightweight and single-component
- High-performance and highly deformable
- Long open time, extended coverage and superior transfer properties to enhance back-buttering, which is ideal for thin porcelain tiles
- Exceeds ANSI A118.4HE and ANSI A118.15HE

ISO 13007 C2ES2P2



	Product Code	Color	Packaging
U.S.	1199311	Gray	Bag: 25 lbs. (11.3 kg)
	1199211	White	Bag: 25 lbs. (11.3 kg)
Canada	1199311CAN	Gray	Bag: 25 lbs. (11.3 kg)
	1199211CAN	White	Bag: 25 lbs. (11.3 kg)



## Ultraflex® LFT™ CO<sub>2</sub> FULLY OFFSET IN THE ENTIRE LIFE CYCLE\*

Still the industry leader for large-format tile, Ultraflex LFT stands up to the rigors of setting large and heavy tiles.

- Nonsag for installing large-format and heavy tile; allows bond coats up to 1/2" (12 mm) thick
- Polymer-enriched for high-performance adhesion and deformability
- Formulated with Easy Glide Technology™ for ease of application
- Exceeds ANSI A118.4HET and ANSI A118.15HET

ISO 13007 C2TES1P1



	Product Code	Color	Packaging
U.S.	2905323	Gray	Bag: 50 lbs. (22.7 kg)
	2905423	White	Bag: 50 lbs. (22.7 kg)
Canada	2905323CAN	Gray	Bag: 50 lbs. (22.7 kg)
	2905423CAN	White	Bag: 50 lbs. (22.7 kg)



## Ultrabond ECO® GPT

This innovative, hybrid-polymer-based adhesive technology saves time and effort during installation of panels/slabs on walls.

- Nonsag performance with panels
- Ready to use, with no mixing required
- Smooth consistency and easy to trowel
- High bond strength and deformability

	Product Code	Packaging
U.S. / Canada	3584615	Pail: 4 U.S. gals. (15.1 L)



## Kerapoxy® 410

When only the best will do, Kerapoxy 410 bonds to urethane/epoxy mesh backings, exterior walls and everywhere in between.

- Solvent-free, 100%-solids, epoxy setting floor and wall mortar that is suited for areas where the most chemical-resistant setting material is necessary
- Has high compressive strength, which provides excellent impact strength in commercial facilities
- Designed for setting most types of tile and stone, including moisture-sensitive stone
- Exceeds ANSI A118.3

ISO 13007 R2

	Product Code	Packaging
U.S.	7491811	Kit: 3 U.S. gals. (11.4 L)
Canada	7491811CAN	Kit: 3 U.S. gals. (11.4 L)







	Product Code	Packaging
U.S. /	6BU5XXX05 <sup>†</sup>	Bag: 10 lbs. (4.54 kg)
Canada	6BU5XXX11 <sup>†</sup>	Bag: 25 lbs. (11.3 kg)

## **Ultracolor® Plus FA** CO<sub>2</sub> FULLY OFFSET IN THE ENTIRE LIFE CYCLE\*


Small grout joints are no problem for the fine aggregate in *Ultracolor Plus FA* grout.

- For joint widths from 1/16" to 3/4" (1.5 to 19 mm)
- Fine-aggregate, fast-setting, polymer-modified, color-consistent, nonshrinking, efflorescence-free grout
- DropEffect™ technology reduces surface absorption to help repel water, dirt and grime from penetrating grout joints.

ISO 13007 CG2WAF



<sup>†</sup> For the "XXX" portion of the product code, use the three-digit number of the desired grout color.



	Product Code	Packaging
U.S. /	4KA5XXX04 <sup>††</sup>	Pail: 1 U.S. gal. (3.79 L)
Canada	4KA5XXX08 <sup>††</sup>	Pail: 2 U.S. gals. (7.57 L)


## **MAPEI Flexcolor® CQ**

For the ultimate in color consistency and installation speed, *MAPEI Flexcolor CQ* grout has you covered.

- For joint widths from 1/16" to 1/2" (1.5 to 12 mm)
- Ready-to-use with quartz aggregate, which ensures color consistency, ease of cleanability and improved workability
- Can be used on sensitive tile surfaces once tested, requires no sealer and cures naturally from evaporation of the low level of water in the formulation
- Exceeds ANSI A118.19



<sup>††</sup> For the "5XXX" portions of the product code, use the four-digit number of the desired grout color.



	Product Code	Packaging
U.S. /	5UB5XXX04 <sup>†††</sup>	1 U.S. gal. (3.79 L)
Canada	5UB5XXX08 <sup>†††</sup>	2 U.S. gals. (7.57 L)

## **Kerapoxy® CQ**

As a grout highly resistant to stains, traffic and most chemicals, *Kerapoxy CQ* grout also protects the delicate edges of gauged tiles.

- For joint widths from 1/16" to 3/8" (1.5 to 10 mm)
- Two-component, 100%-solids epoxy grout and mortar that is nonsagging/nonslumping
- Resistant to stain/chemicals, easy to maintain, water-cleanable and easy to apply

ISO 13007 R2/RG



<sup>†††</sup> For the "5XXX" portions of the product code, use the four-digit number of the desired grout color.



	Product Code	Packaging
U.S. /	3BU5XXX4 <sup>††††</sup>	Cartridge: 10.1 U.S. oz. (299 mL)
Canada		

## **Mapesil® T Plus**

Color-matched to MAPEI's grouts, *Mapesil T Plus* can be used in every joint if needed, including soft joints to accommodate movement.

- 100%-silicone sealant for use on multiple substrates
- Specifically formulated for heavy traffic and expansion/movement joints
- Exceeds ASTM and ANSI standards



<sup>††††</sup> For the "5XXX" portions of the product code, use the four-digit number of the desired color.



Gauged porcelain tile panels require specialized installation products to ensure full mortar coverage and a lifetime of low-maintenance beauty.

While this brochure highlights several options designed specifically for gauged porcelain tile panels, other solutions may be available. Contact your MAPEI representative for more information.



## HIGH-PERFORMANCE SYSTEMS WITH BUILT-IN CONFIDENCE



### MAPEI's System Warranties

System warranties from MAPEI provide enhanced coverage, including replacement product and reimbursement of associated replacement costs. When considering a system warranty, the customer and the MAPEI representative should review the MAPEI products applicable for each category of the installation – such as surface preparation, waterproofing, mortars and grouts. For any installation exceeding 10,000 square feet (929 m<sup>2</sup>), contact MAPEI's Technical Services Department to confirm the system recommendations.

### Special Circumstance Warranties

Commercial and residential contractors can contact their distributor to locate a MAPEI sales representative, who can provide a project warranty when it is a required contract document. All project warranties must be requested prior to the start of the installation.



MAPEI USA  
MAPEI Caribe  
MAPEI Canada

### MAPEI Headquarters of North America

1144 East Newport Center Drive  
Deerfield Beach, Florida 33442  
1-888-US-MAPEI (1-888-876-2734) /  
(954) 246-8888

### Technical Services

1-800-992-6273 (U.S. and Puerto Rico)  
1-800-361-9309 (Canada)

### Customer Service

1-800-42-MAPEI (1-800-426-2734)

Copyright ©2024 by MAPEI Corporation ("MAPEI") and all rights are reserved. All intellectual property rights and other information contained in this document are the exclusive property of MAPEI (or its parent or related companies), unless otherwise noted. No part of this document may be reproduced or transmitted in any form without the prior written consent of MAPEI.

Printed in the USA.

