Safety Data Sheet PLANILEVEL 560

Safety Data Sheet dated: 09/21/2023 - version 2

Date of first edition: 10/28/2022

MAPEI

1. IDENTIFICATION

Product identifier

Mixture identification:

Trade name: PLANILEVEL 560

Trade code: 9003489

Recommended use of the chemical and restrictions on use

Recommended use: Cement based levelling mortar

Restrictions on use: Not available

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Company: MAPEI CORP. (USA and Puerto Rico)

1144 East Newport Center Drive - 33442 - Deerfield Beach - FL - USA

Phone: 954-246-8888

Responsible: RDProductSafety@mapei.com

Emergency 24 hour numbers:

Emergency Number (USA/Canada) CHEMTREC 1(800) 424-9300 / 1(703) 527-3887

Emergency Transport CANUTEC (Canada) 1-613-996-6666

2. HAZARD(S) IDENTIFICATION







Classification of the chemical

Skin corrosion, Category 1A Causes severe skin burns and eye damage.

Serious eye damage, Category 1 Causes serious eye damage.

Skin Sensitization, Category 1 May cause an allergic skin reaction.

Carcinogenicity, Category 1A May cause cancer if inhaled.

Specific target organ toxicity following repeated exposure, Causes damage to organs t

Specific target organ toxicity rollowing repeated exposure,

Category 1

Causes damage to organs through prolonged or repeated exposure if

inhaled.

Label elements

Hazard pictograms and Signal Word



Danger

Hazard statements

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage. H350 May cause cancer if inhaled.

H372 Causes damage to organs through prolonged or repeated exposure if inhaled.

Precautionary statements

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe dust.

P264 Wash hands thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

 ${\sf P301+P330+P33}\ \ {\sf IF}\ {\sf SWALLOWED};\ {\sf rinse}\ \ {\sf mouth}.\ {\sf Do}\ \ {\sf NOT}\ \ {\sf induce}\ \ {\sf vomiting}.$

1

Print date 06/10/2024 Production Name PLANILEVEL 560 Page n. 1 of 10

P302+P352 IF ON SKIN: Wash with plenty of water.

P303+P361+P35 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

2

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P33 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P310 Immediately call a doctor.

P321 Specific treatment (see supplementary instructions on this label).
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with applicable regulations.

Ingredient(s) with unknown acute toxicity:

None

Hazards not otherwise classified identified during the classification process:

None

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances

Not Relevant

Mixtures

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

List of components

Qty	Name	Ident. Numb.	Classification	Registration Number
25-50 %	silica sand; quartz	CAS:14808-60-7 EC:238-878-4	STOT RE 1, H372; Carc. 1A, H350	
5-10 %	portland cement; cement, portland, chemicals	CAS:65997-15-1 EC:266-043-4	STOT SE 3, H335; Eye Dam. 1, H318; Skin Sens. 1, H317; Skin Corr. 1A, H314	
5-10 %	calcium oxide; quicklime	CAS:1305-78-8 EC:215-138-9	Skin Irrit. 2, H315; STOT SE 3, H335; Eye Dam. 1, H318	
2.5-5 %	aluminum sulfate; dialuminum sulfate	CAS:10043-01- 3, 7784-31-8, 16828-12-9 EC:233-135-0	Met. Corr. 1, H290; Eye Dam. 1, H318	01-2119531538-36-XXXX

4. FIRST AID MEASURES

Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

OBTAIN IMMEDIATE MEDICAL ATTENTION.

Obtain medical attention if skin related symptoms persist.

Remove contaminated clothing immediately and dispose of safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an opthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

If breathing is irregular or stopped, administer artificial respiration.

In case of inhalation, consult a doctor immediately and show him packing or label.

Most important symptoms/effects, acute and delayed

Eye irritation

Print date 06/10/2024 Production Name PLANILEVEL 560 Page n. 2 of 10

Erythema

Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

(see paragraph 4.1)

5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media:

Water.

Carbon dioxide (CO2).

Unsuitable extinguishing media:

None in particular.

Specific hazards arising from the chemical

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products: Not available

Explosive properties: Not available Oxidizing properties: Not available

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Limit leakages with earth or sand.

Methods and material for containment and cleaning up

Take up mechanically and dispose of according to local/state/federal regulations

Scoop into containers and seal for disposal.

Retain contaminated washing water and dispose it.

7. HANDLING AND STORAGE

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Exercise the greatest care when handling or opening the container.

Use localized ventilation system.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

Conditions for safe storage, including any incompatibilities

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

Storage temperature: Not available

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Print date 06/10/2024 Production Name PLANILEVEL 560 Page n. 3 of 10

Community Occupational Exposure Limits (OEL)

,	OEL Type	Country	Occupational Exposure Limit
silica sand; quartz CAS: 14808-60-7	ACGIH		Long Term: 0.025 mg/m3 A2 - Suspected Human Carcinogen;lung cancer;pulmonary fibrosis;
	ACGIH		Long Term: 0.025 mg/m3 A2 - Suspected Human Carcinogen;lung cancer;pulmonary fibrosis
	MAK	AUSTRIA	Long Term: 0.15 mg/m3
	MAK	SWITZERLAN D	Long Term: 0.15 mg/m3
portland cement; cement, portland, chemicals CAS: 65997-15-1	OSHA		Long Term: 15 mg/m3
	OSHA		Long Term: 5 mg/m3
	ACGIH		Long Term: 1 mg/m3 A4 - Not Classifiable as a Human Carcinogen;pulmonary function;respiratory symptoms;asthma;
	ACGIH		Long Term: 1 mg/m3 A4 - Not Classifiable as a Human Carcinogen;pulmonary function;respiratory symptoms;asthma
	MAK	AUSTRIA	Long Term: 5 mg/m3
	MAK		Long Term: 5 mg/m3
calcium oxide; quicklime CAS: 1305-78-8	OSHA		Long Term: 5 mg/m3
	ACGIH		Long Term: 2 mg/m3 upper respiratory tract irritation;
	MAK	GERMANY	Long Term: 1 mg/m3
	ACGIH		Long Term: 2 mg/m3 upper respiratory tract irritation
	MAK	AUSTRIA	Long Term: 1 mg/m3; Short Term: 4 mg/m3
	MAK	SWITZERLAN D	Long Term: 2 mg/m3
	MAK	SWITZERLAN D	Long Term: 1 mg/m3

Predicted No Effect Concentration (PNEC) values

Exposure Route: Fresh Water; PNEC Limit: 0.0003 mg/l aluminum sulfate; dialuminum sulfate

CAS: 10043-01-3, 7784-31-8, 16828-12-9

Exposure Route: Marine water; PNEC Limit: 0.00003 mg/l

Derived No Effect Level (DNEL) values

aluminum sulfate; dialuminum sulfate

Exposure Route: Human Dermal; Exposure Frequency: Long Term (repeated)

Worker Industry: 3.8 mg/kg

CAS: 10043-01-3, 7784-31-8, 16828-12-9

Exposure Route: Human Inhalation; Exposure Frequency: Long Term (repeated)

Worker Industry: 13.4 mg/m3; Consumer: 3.3 mg/m3

Exposure Route: Human Oral; Exposure Frequency: Long Term (repeated)

Consumer: 1.9 mg/kg

Appropriate engineering controls: Not available

Individual protection measures

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

06/10/2024 PLANILEVEL 560 Print date Production Name Page n. 4 of 10

Protection for hands:

Suitable materials for safety gloves; 29 CFR 1910.138 - ANSI/ISEA 105: Polychloroprene - CR: thickness >=0,5mm; breakthrough time >=480min. Nitrile rubber - NBR: thickness >=0,35mm; breakthrough time >=480min. Butyl rubber - IIR: thickness >=0,5mm; breakthrough time >=480min.

Fluorinated rubber - FKM: thickness >=0,4mm; breakthrough time >=480min.

Use impervious gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Respiratory protection must be used where exposure levels exceed workplace exposure limits. Refer to 29 CFR 1910.134 - CSA Z94.4 for information on selection and use of appropriate respiratory protection equipment.

Use adequate protective respiratory equipment.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state: Solid

Appearance and colour: powder grey

Odour: cement like

Odour threshold: No data available

pH: No data available

pH (water dispersion, 10%): 10.00

Melting point / freezing point: No data available

Initial boiling point and boiling range: No data available

Flash point: Not Applicable

Evaporation rate: No data available

Upper/lower flammability or explosive limits: No data available

Vapour density: No data available Vapour pressure: No data available Relative density: No data available Solubility in water: dispersible Solubility in oil: No data available

Partition coefficient (n-octanol/water): No data available

Auto-ignition temperature: No data available Decomposition temperature: No data available

Viscosity: No data available

Explosive properties: No data available Oxidizing properties: No data available Solid/gas flammability: No data available

Other information

Substance Groups relevant properties No data available

Miscibility: No data available Fat Solubility: No data available Conductivity: No data available

10. STABILITY AND REACTIVITY

Reactivity

Stable under normal conditions

Chemical stability

Data not available.

Possibility of hazardous reactions

None.

Conditions to avoid

Stable under normal conditions.

Incompatible materials

None in particular.

Hazardous decomposition products

None.

11. TOXICOLOGICAL INFORMATION

Information on toxicological effects

Toxicological Information of the Preparation

Print date 06/10/2024 Production Name PLANILEVEL 560 Page n. 5 of 10

a) acute toxicity Not classified

b) skin corrosion/irritation

c) serious eye damage/irritation

Based on available data, the classification criteria are not met The product is classified: Skin corrosion, Category 1A(H314) The product is classified: Serious eye damage, Category 1(H318) d) respiratory or skin sensitisation The product is classified: Skin Sensitization, Category 1(H317)

e) germ cell mutagenicity Not classified

Based on available data, the classification criteria are not met

f) carcinogenicity The product is classified: Carcinogenicity, Category 1A(H350)

g) reproductive toxicity Not classified

Based on available data, the classification criteria are not met

h) STOT-single exposure Not classified

Based on available data, the classification criteria are not met

The product is classified: Specific target organ toxicity following repeated exposure, i) STOT-repeated exposure

Category 1(H372)

j) aspiration hazard Not classified

Based on available data, the classification criteria are not met

Toxicological information on main components of the mixture:

silica sand; quartz a) acute toxicity LD50 Oral Rat = 500 mg/kg

calcium oxide; quicklime a) acute toxicity LD50 Oral Rat = 500 mg/kg

LC50 Inhalation Rat > 6.04 mg/l 4h

aluminum sulfate;

dialuminum sulfate

a) acute toxicity

LD50 Oral Rat > 2000 mg/kg

LD50 Skin Rabbit > 5000 mg/kg LC50 Inhalation Rat > 5000 mg/m3

Substance(s) listed on the IARC Monographs:

silica sand; quartz

Substance(s) listed as OSHA Carcinogen(s):

silica sand; quartz

Substance(s) listed as NIOSH Carcinogen(s):

silica sand; quartz

Substance(s) listed on the NTP report on Carcinogens:

silica sand; quartz

12. ECOLOGICAL INFORMATION

Toxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

List of Eco-Toxicological properties of the product

Not classified for environmental hazards.

Based on available data, the classification criteria are not met

List of Eco-Toxicological properties of the components

Component Ident. Numb. **Ecotox Data**

silica sand; quartz CAS: 14808-60- a) Aquatic acute toxicity: LC50 carp > 10000 mg/L 72h

7 - EINECS: 238-878-4

calcium oxide; quicklime CAS: 1305-78-8 a) Aquatic acute toxicity: LC50 Fish Cyprinus carpio = 1070 mg/L 96h IUCLID

- EINECS: 215-

138-9

CAS: 10043-01- a) Aquatic acute toxicity: LC50 Fish = 104 mg/L 96 aluminum sulfate; dialuminum

sulfate 3, 7784-31-8,

Print date 06/10/2024 Production Name PLANILEVEL 560 6 of 10 Page n.

16828-12-9 -EINECS: 233-135-0

a) Aquatic acute toxicity: NOEC Fish > 1000 mg/L 96
 a) Aquatic acute toxicity: EC50 Daphnia = 48 mg/L 48
 a) Aquatic acute toxicity: NOEC Daphnia > 160 mg/L 48

a) Aquatic acute toxicity: LC50 Fish Pimephales promelas = 27.9 mg/L 96h

ECHA

Persistence and degradability

N.A.

Bioaccumulative potential

N.A.

Mobility in soil

N.A.

Other adverse effects

N.A.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

The generation of waste should be avoided or minimized wherever possible. Recover if possible.

Methods of disposal:

Disposal of this product, solutions, packaging and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor.

Do not dispose of waste into sewers.

Disposal considerations:

Do not allow to enter drains or watercourses.

Dispose of product according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions. For further information, contact your local waste authority.

Special precautions:

This material and its container must be disposed of in a safe way. Care should be taken when handling untreated empty containers. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Empty containers or liners may retain some product residues. Do not re-use empty containers.

14. TRANSPORT INFORMATION

Not classified as dangerous in the meaning of transport regulations.

UN number

DOT-UN Number: Not Applicable ADR-UN number: Not Applicable IATA-Un number: Not Applicable IMDG-Un number: Not Applicable

UN proper shipping name

DOT-Proper Shipping Name: Not Applicable ADR-Shipping Name: Not Applicable IATA-Technical name: Not Applicable IMDG-Technical name: Not Applicable

Transport hazard class(es)

DOT-Hazard Class: Not Applicable ADR-Class: Not Applicable IATA-Class: Not Applicable IMDG-Class: Not Applicable

Packing group

DOT Packing Group: Not Applicable ADR-Packing Group: Not Applicable IATA-Packing group: Not Applicable IMDG-Packing group: Not Applicable

Print date 06/10/2024 Production Name PLANILEVEL 560 Page n. 7 of 10

Environmental hazards

Marine pollutant: No

Environmental Pollutant: Not Applicable

DOT-RQ: Yes DOT-RQ - Quantity: 5000 lbs

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not Applicable

Special precautions

Department of Transportation (DOT):

Not Applicable

Road and Rail (ADR-RID):

Not Applicable

Air (IATA):

Not Applicable

Sea (IMDG):

Not Applicable

15. REGULATORY INFORMATION

USA - Federal regulations

TSCA - Toxic Substances Control Act

All the components are listed on the TSCA inventory

TSCA listed substances:

silica sand; quartz portland cement; cement,

portland, chemicals

is listed in TSCA Section 8b is listed in TSCA Section 8b

calcium oxide; quicklime is listed in TSCA Section 8b aluminum sulfate; dialuminum

is listed in TSCA Section 8b

sulfate

SARA - Superfund Amendments and Reauthorization Act

Section 302 - Extremely Hazardous Substances:

No substances listed

Section 304 - Hazardous substances:

aluminum sulfate; dialuminum sulfate

Section 313 - Toxic chemical list:

No substances listed

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

Substance(s) listed under CERCLA:

aluminum sulfate; dialuminum sulfate Reportable quantity: 5000 pounds

CAA - Clean Air Act

CAA listed substances:

No substances listed

CWA - Clean Water Act

CWA listed substances:

aluminum sulfate; dialuminum

is listed in CWA Section 311

USA - State specific regulations

California Proposition 65

Substance(s) listed under California Proposition 65:

silica sand; quartz Listed as carcinogen

Massachusetts Right to know

Substance(s) listed under Massachusetts Right to know:

silica sand; quartz

portland cement; cement, portland, chemicals

calcium oxide; quicklime

aluminum sulfate; dialuminum sulfate

Pennsylvania Right to know

Substance(s) listed under Pennsylvania Right to know:

Print date 06/10/2024 **Production Name** PLANILEVEL 560 8 of 10 Page n.

silica sand; quartz

portland cement; cement, portland, chemicals

calcium oxide; quicklime

aluminum sulfate; dialuminum sulfate

New Jersey Right to know

Substance(s) listed under New Jersey Right to know:

silica sand; quartz

portland cement; cement, portland, chemicals

calcium oxide; quicklime

aluminum sulfate; dialuminum sulfate

Canada - Federal regulations

DSL - Domestic Substances List

All the substances are listed in the DSL.

NDSL - Non Domestic Substances List

This product complies with NDSL inventory

NPRI - National Pollutant Release Inventory

NPRI (National Pollutant Release Inventory) - List of substances listed.

No substances listed

16. OTHER INFORMATION

Safety Data Sheet dated: 9/21/2023 - version 2

Additional classification information

NFPA Health: 2 = Moderate

NFPA Flammability: 0 = Not Combustible

NFPA Reactivity: 0 = Minimal NFPA Special Risk: N.A.



NFPA

Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. The information herein is presented in good faith and believed to be accurate as of the effective date given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or provincial, and local laws.

This document was prepared by a competent person who has received appropriate training.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Code	Description
H290	May be corrosive to metals.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H350	May cause cancer.
H372	Causes damage to organs through prolonged or repeated exposure.

Code	Hazard class and hazard category	Description
A.2/1A	Skin Corr. 1A	Skin corrosion, Category 1A
A.2/2	Skin Irrit. 2	Skin irritation, Category 2
A.3/1	Eye Dam. 1	Serious eye damage, Category 1
A.4.2/1	Skin Sens. 1	Skin Sensitization, Category 1
A.6/1A	Carc. 1A	Carcinogenicity, Category 1A
A.8/3	STOT SE 3	Specific target organ toxicity following single exposure, Category 3
A.9/1	STOT RE 1	Specific target organ toxicity following repeated exposure, Category 1
B.16/1	Met. Corr. 1	Chemicals corrosive to metal, Category 1

Legend to abbreviations and acronyms used in the safety data sheet:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

IMDG: International Maritime Code for Dangerous Goods.

IATA: International Air Transport Association.

Print date 06/10/2024 Production Name PLANILEVEL 560 Page n. 9 of 10

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

CLP: Classification, Labeling, Packaging.

EINECS: European Inventory of Existing Commercial Chemical Substances.

INCI: International Nomenclature of Cosmetic Ingredients.

CAS: Chemical Abstracts Service (division of the American Chemical Society).

GefStoffVO: Ordinance on Hazardous Substances, Germany.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

DNEL: Derived No Effect Level.

PNEC: Predicted No Effect Concentration.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

STEL: Short Term Exposure limit.
STOT: Specific Target Organ Toxicity.
WGK: German Water Hazard Class.

KSt: Explosion coefficient.

Paragraphs modified from the previous revision:

- 2. HAZARDS IDENTIFICATION
- 3. COMPOSITION/INFORMATION ON INGREDIENTS
- 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
- 11. TOXICOLOGICAL INFORMATION
- 12. ECOLOGICAL INFORMATION
- 15. REGULATORY INFORMATION
- 16. OTHER INFORMATION

Print date 06/10/2024 Production Name PLANILEVEL 560 Page n. 10of 10