## **Safety Data Sheet EPOJET SLV NA / B**

Safety Data Sheet dated: 06/20/2024 - version 2

Date of first edition: 10/26/2022



## 1. IDENTIFICATION

## **Product identifier**

Mixture identification:

Trade name: EPOJET SLV NA / B

Trade code: 9015613

Recommended use of the chemical and restrictions on use

Recommended use: Hardener for epoxy products

Restrictions on use: Not available

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Company: MAPEI CORP. (USA and Puerto Rico)

1144 East Newport Center Drive - 33442 - Deerfield Beach - FL - USA

Phone: 954-246-8888

Responsable: RDProductSafety@mapei.com

**Emergency 24 hour numbers:** 

Emergency Number (USA/Canada) CHEMTREC 1(800) 424-9300 / 1(703) 527-3887

Emergency Transport CANUTEC (Canada) 1-613-996-6666

## 2. HAZARD(S) IDENTIFICATION





#### Classification of the chemical

Acute toxicity (oral), Category 4 Harmful if swallowed.

Skin corrosion, Category 1A Causes severe skin burns and eye damage.

Causes serious eye damage. Serious eye damage, Category 1

Skin Sensitization, Category 1A May cause an allergic skin reaction.

Harmful to aquatic life with long lasting effects. Chronic (long term) aquatic hazard, category 3

## **Label elements**

## **Hazard pictograms and Signal Word**



Danger

## **Hazard statements**

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction. H318 Causes serious eye damage.

H412 Harmful to aquatic life with long lasting effects.

**Precautionary statements** 

P260 Do not breathe mist/vapours/spray.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P312 IF SWALLOWED: Call a doctor if you feel unwell.

P301+P330+P33 IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P302+P352 IF ON SKIN: Wash with plenty of water.

Print date 01/21/2025 Production Name EPOJET SLV NA / B Page n. 1 of 10 P303+P361+P35 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

3

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P33 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing.

P310 Immediately call a doctor.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

P501 Dispose of contents/container in accordance with applicable regulations.

## Ingredient(s) with unknown acute toxicity:

None

## Hazards not otherwise classified identified during the classification process:

None

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

## **Substances**

Not Relevant

#### **Mixtures**

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

## List of components

Qty	Name	Ident. Numb.	Classification
25-50 %	trimethylhexamethylenediamine; Trimethylhexane-1,6-diamine	CAS:25620-58-0 EC:247-134-8	Acute Tox. 4, H302; Skin Sens. 1, H317; Aquatic Chronic 3, H412; Skin Corr. 1A, H314
25-50 %	3-aminomethyl-3,5,5- trimethylcyclohexylamine	CAS:2855-13-2 EC:220-666-8 Index:612-067-00-9	Acute Tox. 4, H302; Skin Corr. 1B, H314; Eye Dam. 1, H318; Skin Sens. 1A, H317
25-50 %		CAS:112-24-3 EC:203-950-6 Index:612-059-00-5	Skin Sens. 1, H317; Aquatic Chronic 3, H412; Acute Tox. 4, H312; Acute Tox. 4, H302; Skin Corr. 1B, H314
2.5-5 %	2,4,6-tris(dimethylaminomethyl)phenol	CAS:90-72-2 EC:202-013-9 Index:603-069-00-0	Skin Corr. 1C, H314; Eye Dam. 1, H318; Acute Tox. 4, H302
1-2.5 %	benzyl alcohol	CAS:100-51-6 EC:202-859-9 Index:603-057-00-5	Acute Tox. 4, H302; Eye Irrit. 2A, H319

## 4. FIRST AID MEASURES

## **Description of first aid measures**

In case of skin contact:

Immediately take off all contaminated clothing.

OBTAIN IMMEDIATE MEDICAL ATTENTION.

Obtain medical attention if skin related symptoms persist.

Remove contaminated clothing immediately and dispose of safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an opthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Give nothing to eat or drink.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

## Most important symptoms/effects, acute and delayed

Eye irritation Eye damages Skin Irritation

Print date 01/21/2025 Production Name EPOJET SLV NA / B Page n. 2 of 10

## Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

(see paragraph 4.1)

## 5. FIRE-FIGHTING MEASURES

## **Extinguishing media**

Suitable extinguishing media:

Water.

Carbon dioxide (CO2).

## Unsuitable extinguishing media:

None in particular.

## Specific hazards arising from the chemical

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products: Not available

Explosive properties: Not available Oxidizing properties: Not available

## Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

## **6. ACCIDENTAL RELEASE MEASURES**

## Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove persons to safety.

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Limit leakages with earth or sand.

## Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Retain contaminated washing water and dispose it.

## 7. HANDLING AND STORAGE

## Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

## Conditions for safe storage, including any incompatibilities

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

Storage temperature: Not available

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## **Control parameters**

## **Community Occupational Exposure Limits (OEL)**

	OEL Type	Country	Occupational Exposure Limit
benzyl alcohol CAS: 100-51-6	MAK	GERMANY	Long Term: 22 mg/m3 - 5 ppm
	MAK	SWITZERLAN D	Long Term: 22 mg/m3 - 5 ppm

Print date 01/21/2025 Production Name EPOJET SLV NA / B Page n. 3 of 10

## Predicted No Effect Concentration (PNEC) values

3-aminomethyl-3,5,5- Exposure Route: Fresh Water; PNEC Limit: 0.06 mg/l

trimethylcyclohexylamine

CAS: 2855-13-2

Exposure Route: Marine water; PNEC Limit: 0.006 mg/l
Exposure Route: Intermittent release; PNEC Limit: 0.23 mg/l
Exposure Route: Freshwater sediments; PNEC Limit: 5.784 mg/kg
Exposure Route: Marine water sediments; PNEC Limit: 0.578 mg/kg

Exposure Route: Soil; PNEC Limit: 1.121 mg/kg

Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 3.18 mg/l

## **Derived No Effect Level (DNEL) values**

3-aminomethyl-3,5,5- Exposure Route: Human Inhalation trimethylcyclohexylamine Worker Industry: 20.1 mg/m3

CAS: 2855-13-2

2,4,6- Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects

tris Worker Industry: 0.31 mg/m3

(dimethylaminomethyl)

phenol CAS: 90-72-2

Appropriate engineering controls: Not available

#### **Individual protection measures**

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Suitable materials for safety gloves; 29 CFR 1910.138 - ANSI/ISEA 105: Polychloroprene - CR: thickness >=0,5mm; breakthrough time >=480min. Nitrile rubber - NBR: thickness >=0,35mm; breakthrough time >=480min. Butyl rubber - IIR: thickness >=0,5mm; breakthrough time >=480min. Fluorinated rubber - FKM: thickness >=0,4mm; breakthrough time >=480min.

Use impervious gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Respiratory protection must be used where exposure levels exceed workplace exposure limits. Refer to 29 CFR 1910.134 - CSA Z94.4 for information on selection and use of appropriate respiratory protection equipment.

Use adequate protective respiratory equipment.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

## Information on basic physical and chemical properties

Physical state: Liquid

Appearance and colour: Amber

Odour: Characteristic

Odour threshold: No data available

pH: 11.00

Melting point / freezing point: No data available Initial boiling point and boiling range: 100 °C (212 °F)

Flash point: 94 °C (201 °F)

Evaporation rate: No data available

Upper/lower flammability or explosive limits: No data available

Vapour density: No data available Vapour pressure: No data available Relative density: 0.93 g/cm3 Solubility in water: partly soluble

Solubility in oil: insoluble

Partition coefficient (n-octanol/water): No data available

Auto-ignition temperature: No data available Decomposition temperature: No data available

Viscosity: No data available

Kinematic viscosity: > 20,5 mm2/sec (40 °C) mm2/s

Explosive properties: No data available

Print date 01/21/2025 Production Name EPOJET SLV NA / B Page n. 4 of 10

Oxidizing properties: No data available Solid/gas flammability: No data available

#### Other information

Substance Groups relevant properties No data available

Miscibility: No data available Fat Solubility: No data available Conductivity: No data available

## 10. STABILITY AND REACTIVITY

#### Reactivity

Stable under normal conditions

## **Chemical stability**

Data not available.

#### Possibility of hazardous reactions

None.

## **Conditions to avoid**

Stable under normal conditions.

## **Incompatible materials**

None in particular.

## Hazardous decomposition products

None.

## 11. TOXICOLOGICAL INFORMATION

## Information on toxicological effects

## **Toxicological Information of the Preparation**

a) acute toxicity The product is classified: Acute toxicity (oral), Category 4(H302)

ATEmix - Oral: 743.048 mg/kg bw

b) skin corrosion/irritation The product is classified: Skin corrosion, Category 1A(H314)
c) serious eye damage/irritation The product is classified: Serious eye damage, Category 1(H318)
d) respiratory or skin sensitisation The product is classified: Skin Sensitization, Category 1A(H317)

e) germ cell mutagenicity Not classified

Based on available data, the classification criteria are not met

f) carcinogenicity Not classified

Based on available data, the classification criteria are not met

g) reproductive toxicity Not classified

Based on available data, the classification criteria are not met

h) STOT-single exposure Not classified

Based on available data, the classification criteria are not met

i) STOT-repeated exposure Not classified

Based on available data, the classification criteria are not met

j) aspiration hazard Not classified

Based on available data, the classification criteria are not met

## Toxicological information on main components of the mixture:

trimethylhexamethylenedi a) acute toxicity

amine; Trimethylhexane-1,6-diamine LD50 Oral Rat = 910 mg/kg

3-aminomethyl-3,5,5- a) acute toxicity

trimethylcyclohexylamine

LC50 Inhalation Dust Rat > 5.01 mg/l 4h

LD50 Oral Rat = 1030 mg/kgLD50 Skin Rat > 2000 mg/kg

a) acute toxicity LD50 Skin Rabbit = 550 mg/kg

LD50 Oral Rat = 2500 mg/kg LD50 Skin Rabbit = 550 mg/kg LD50 Oral Rat = 2500 mg/kg

Print date 01/21/2025 Production Name EPOJET SLV NA / B Page n. 5 of 10

2,4,6- a) acute toxicity LD50 Oral Rat = 2169 mg/kg

tris

(dimethylaminomethyl)

phenol

LD50 Skin Rat > 1 ml/kg

benzyl alcohol a) acute toxicity LD50 Oral Rat = 1620 mg/kg

Substance(s) listed on the IARC Monographs:

None

Substance(s) listed as OSHA Carcinogen(s):

None

Substance(s) listed as NIOSH Carcinogen(s):

None

Substance(s) listed on the NTP report on Carcinogens:

None

## 12. ECOLOGICAL INFORMATION

## **Toxicity**

Adopt good working practices, so that the product is not released into the environment. Eco-Toxicological Information:

## List of Eco-Toxicological properties of the product

The product is classified: Chronic (long term) aquatic hazard, category 3(H412)

list of For Torrigal wind words			
List of Eco-Toxicological prope Component	rties of the comp Ident. Numb.	Ecotox Data	
trimethylhexamethylenediamine; Trimethylhexane-1,6-diamine			EC50 Algae Desmodesmus subspicatus = 29.5 mg/L
		a) Aquatic acute toxicity :	EC50 daphnia magna = 31.5 mg/L - 24h
		a) Aquatic acute toxicity :	LC50 Algae leuciscus idus = 172 mg/L 48h - Static
3-aminomethyl-3,5,5- trimethylcyclohexylamine	CAS: 2855-13-2 - EINECS: 220- 666-8 - INDEX: 612-067-00-9	a) Aquatic acute toxicity :	LC50 Fish = 110 mg/L 96
		a) Aquatic acute toxicity :	EC50 Daphnia = 23 mg/L 48
		a) Aquatic acute toxicity :	EC50 Daphnia = 388 mg/L 48
		a) Aquatic acute toxicity:	EC50 Algae > 50 mg/L 72
		b) Aquatic chronic toxicity	: NOEC Daphnia = 3 mg/L - 21 d
		a) Aquatic acute toxicity:	EC50 Daphnia Daphnia magna 14.6 mg/L 48h EPA
		a) Aquatic acute toxicity: 72h IUCLID	EC50 Algae Desmodesmus subspicatus = 37 mg/L
	CAS: 112-24-3 - EINECS: 203- 950-6 - INDEX: 612-059-00-5	a) Aquatic acute toxicity : IUCLID	LC50 Fish Poecilia reticulata = 570 mg/L 96h
		a) Aquatic acute toxicity : IUCLID	LC50 Fish Pimephales promelas = 495 mg/L 96h
		a) Aquatic acute toxicity : 72h IUCLID	EC50 Algae Desmodesmus subspicatus = 2.5 mg/L
		a) Aquatic acute toxicity : mg/L 72h IUCLID	EC50 Algae Pseudokirchneriella subcapitata = 20
		a) Aquatic acute toxicity:	EC50 Algae Pseudokirchneriella subcapitata = 3.7

Print date 01/21/2025 Production Name EPOJET SLV NA / B Page n. 6 of 10

mg/L 96h EPA

a) Aquatic acute toxicity: EC50 Daphnia Daphnia magna = 31.1 mg/L 48h

2,4,6-CAS: 90-72-2 -

tris(dimethylaminomethyl)phenol EINECS: 202-

013-9 - INDEX: 603-069-00-0

> a) Aquatic acute toxicity: EC50 Algae = 46.7 mg/L 72h a) Aquatic acute toxicity: NOEC Algae = 25.1 mg/L 72h

a) Aquatic acute toxicity: LC50 Fish = 175 mg/L 96h

CAS: 100-51-6 - a) Aquatic acute toxicity: LC50 Fish Pimephales promelas = 460 mg/L 96h benzyl alcohol

EINECS: 202-

859-9 - INDEX: 603-057-00-5

## Persistence and degradability

N.A.

## **Bioaccumulative potential**

N.A.

## Mobility in soil

## Other adverse effects

N.A.

## 13. DISPOSAL CONSIDERATIONS

## **Waste treatment methods**

The generation of waste should be avoided or minimized wherever possible. Recover if possible.

#### Methods of disposal:

Disposal of this product, solutions, packaging and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor.

Do not dispose of waste into sewers.

## Disposal considerations:

Do not allow to enter drains or watercourses.

Dispose of product according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be

Dispose of containers contaminated by the product in accordance with local or national legal provisions. For further information, contact your local waste authority.

## Special precautions:

This material and its container must be disposed of in a safe way. Care should be taken when handling untreated empty containers. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Empty containers or liners may retain some product residues. Do not re-use empty containers.

## 14. TRANSPORT INFORMATION

## **UN** number

DOT-UN Number: UN2735 ADR-UN number: 2735 IATA-Un number: 2735 IMDG-Un number: 2735

## **UN proper shipping name**

DOT-Proper Shipping Name: AMINES, LIQUID, CORROSIVE, N.O.S. (trimethylhexamethylenediamine - isophoronediamine) ADR-Shipping Name: AMINES, LIQUID, CORROSIVE, N.O.S. (trimethylhexamethylenediamine - isophoronediamine) IATA-Technical name: AMINES, LIQUID, CORROSIVE, N.O.S. (trimethylhexamethylenediamine - isophoronediamine) IMDG-Technical name: AMINES, LIQUID, CORROSIVE, N.O.S. (trimethylhexamethylenediamine - isophoronediamine)

## Transport hazard class(es)

DOT-Hazard Class: 8

ADR-Class: 8 IATA-Class: 8 IMDG-Class: 8

## **Packing group**

Print date 01/21/2025 **EPOJET SLV NA / B** 7 of 10 Production Name Page n.

DOT Packing Group: III ADR-Packing Group: III IATA-Packing group: III IMDG-Packing group: III

## **Environmental hazards**

Marine pollutant: No

Environmental Pollutant: Not Applicable

DOT-RQ: No

## Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not Applicable

## Special precautions

Department of Transportation (DOT):

DOT-Special Provision(s): IB3, T7, TP1, TP28

DOT-Label(s): 8 DOT-Symbol: N/A DOT-Cargo Aircraft: N/A DOT-Passenger Aircraft: N/A

DOT-Bulk: N/A DOT-Non-Bulk: N/A

DOT-Limited Quantity threshold: 5 L

Road and Rail (ADR-RID):

ADR exempt: No ADR-Label: 8

ADR-Hazard identification number: 80

ADR-Transport category (Tunnel restriction code): 3 (E)

Air (IATA):

IATA-Passenger Aircraft: 852 IATA-Cargo Aircraft: 856

IATA-Label: 8

IATA-Subsidiary hazards: -

IATA-Erg: 8L

IATA-Special Provisions: A3 A803

Sea (IMDG):

IMDG-Stowage Code: Category A IMDG-Stowage Note: SG35 SGG18

IMDG-Subsidiary hazards: -

IMDG-Special Provisions: 223 274

IMDG-EMS: F-A, S-B

## 15. REGULATORY INFORMATION

## **USA - Federal regulations**

## **TSCA - Toxic Substances Control Act**

**TSCA listed substances:** 

trimethylhexamethylenediamine; is listed in TSCA Section 8b

Trimethylhexane-1,6-diamine

3-aminomethyl-3,5,5is listed in TSCA Section 8b

trimethylcyclohexylamine

is listed in TSCA Section 8b

2,4,6is listed in TSCA Section 8b

tris(dimethylaminomethyl)phenol

is listed in TSCA Section 8b benzyl alcohol

## **SARA - Superfund Amendments and Reauthorization Act**

Section 302 - Extremely Hazardous Substances:

No substances listed

## Section 304 - Hazardous substances:

No substances listed

Print date 01/21/2025 Production Name EPOJET SLV NA / B 8 of 10 Page n.

## Section 313 - Toxic chemical list:

No substances listed

# CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act Substance(s) listed under CERCLA:

No substances listed

CAA - Clean Air Act

**CAA listed substances:** 

benzyl alcohol is listed in CAA Section 112(b) - HON

**CWA - Clean Water Act** 

**CWA listed substances:** 

No substances listed

## **USA - State specific regulations**

**California Proposition 65** 

Substance(s) listed under California Proposition 65:

No substances listed

Massachusetts Right to know

Substance(s) listed under Massachusetts Right to know:

benzyl alcohol

#### Pennsylvania Right to know

#### Substance(s) listed under Pennsylvania Right to know:

trimethylhexamethylenediamine; Trimethylhexane-1,6-diamine

benzyl alcohol

## New Jersey Right to know

## Substance(s) listed under New Jersey Right to know:

trimethylhexamethylenediamine; Trimethylhexane-1,6-diamine

3-aminomethyl-3,5,5-trimethylcyclohexylamine

## Canada - Federal regulations

**DSL - Domestic Substances List** 

**NDSL - Non Domestic Substances List** 

**NPRI - National Pollutant Release Inventory** 

NPRI (National Pollutant Release Inventory) - List of substances listed.

No substances listed

## **16. OTHER INFORMATION**

Safety Data Sheet dated: 6/20/2024 - version 2

Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. The information herein is presented in good faith and believed to be accurate as of the effective date given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or provincial, and local laws.

This document was prepared by a competent person who has received appropriate training.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Code	Hazard class and hazard category Description		
H412	Harmful to aquatic life with long lasting effects.		
H319	Causes serious eye irritation.		
H318	Causes serious eye damage.		
H317	May cause an allergic skin reaction.		
H314	Causes severe skin burns and eye damage.		
H312	Harmful in contact with skin.		
H302	Harmful if swallowed.		
Code	Description		

Print date 01/21/2025 Production Name EPOJET SLV NA / B Page n. 9 of 10

A.1/4/Dermal Acute toxicity (dermal), Category 4 Acute Tox. 4 A.1/4/Oral Acute Tox. 4 Acute toxicity (oral), Category 4 A.2/1A Skin Corr. 1A Skin corrosion, Category 1A A.2/1B Skin Corr. 1B Skin corrosion, Category 1B A.2/1C Skin Corr. 1C Skin corrosion, Category 1C A.3/1Eye Dam. 1 Serious eye damage, Category 1 A.3/2A Eye Irrit. 2A Eye irritation, Category 2A A.4.2/1Skin Sens. 1 Skin Sensitization, Category 1 A.4.2/1A Skin Sens. 1A Skin Sensitization, Category 1A

US-HAE/C3 Aquatic Chronic 3 Chronic (long term) aquatic hazard, category 3

## Legend to abbreviations and acronyms used in the safety data sheet:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

IMDG: International Maritime Code for Dangerous Goods.

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

CLP: Classification, Labeling, Packaging.

EINECS: European Inventory of Existing Commercial Chemical Substances.

INCI: International Nomenclature of Cosmetic Ingredients.

CAS: Chemical Abstracts Service (division of the American Chemical Society).

GefStoffVO: Ordinance on Hazardous Substances, Germany. LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

DNEL: Derived No Effect Level.

PNEC: Predicted No Effect Concentration.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

STEL: Short Term Exposure limit. STOT: Specific Target Organ Toxicity. WGK: German Water Hazard Class.

KSt: Explosion coefficient.

## Paragraphs modified from the previous revision:

- 2. HAZARDS IDENTIFICATION
- 3. COMPOSITION/INFORMATION ON INGREDIENTS
- 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
- 9. PHYSICAL AND CHEMICAL PROPERTIES
- 11. TOXICOLOGICAL INFORMATION
- 12. FCOLOGICAL INFORMATION
- 14. TRANSPORT INFORMATION
- 15. REGULATORY INFORMATION
- 16. OTHER INFORMATION

Print date 01/21/2025 EPOJET SLV NA / B 10of 10 Production Name Page n.