Safety Data Sheet RESFOAM HB 45

Safety Data Sheet dated: 12/10/2024 - version 7

Date of first edition: 09/02/2015

MAPEI

1. IDENTIFICATION

Product identifier used on the label

Mixture identification:

Trade name: RESFOAM HB 45

Trade code: 9024453

Recommended use of the chemical and restrictions on use

Recommended use: Polyurethanic coating

Restrictions on use: Not available

Name, U.S. address, and U.S. telephone number of the chemical manufacturer, importer, or other responsible party

Company: MAPEI CORP. (USA and Puerto Rico)

1144 East Newport Center Drive - 33442 - Deerfield Beach - FL - USA

Phone: 954-246-8888

Responsable: RDProductSafety@mapei.com

Emergency 24 hour numbers:

Emergency Number (USA/Canada) CHEMTREC 1(800) 424-9300 / 1(703) 527-3887

Emergency Transport CANUTEC (Canada) 1-613-996-6666

2. HAZARD(S) IDENTIFICATION







Classification of the chemical

Skin irritation, Category 2 Causes skin irritation.

Eye irritation, Category 2A Causes serious eye irritation.

Respiratory Sensitization, Category 1 May cause allergy or asthma symptoms or breathing difficulties if

inhaled

Skin Sensitization, Category 1 May cause an allergic skin reaction.

Carcinogenicity, Category 2 Suspected of causing cancer if inhaled, in contact with skin and if

swallowed.

Specific target organ toxicity following single exposure,

Category 3

May cause respiratory irritation.

Specific target organ toxicity following repeated exposure,

Category 2

May cause damage to organs through prolonged or repeated exposure

if inhaled, in contact with skin and if swallowed.

Very toxic to aquatic life.

Acute aquatic hazard, category 1

Hazard pictograms and Signal Word



Label elements

Danger

Hazard statements

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H351 Suspected of causing cancer if inhaled, in contact with skin and if swallowed.

H373 May cause damage to organs through prolonged or repeated exposure if inhaled, in contact with skin and

if swallowed.

H400 Very toxic to aquatic life.

Print date 08/26/2025 Production Name RESFOAM HB 45 Page n. 1 of 12

Precautionary statements

	P201	Obtain special instructions before use.			
	P202	Do not handle until all safety precautions have been read and understood.			
	P260	Do not breathe mist/vapours/spray.			
	P264	Wash skin thoroughly after handling.			
	P271	Use only outdoors or in a well-ventilated area.			
	P273	Avoid release to the environment.			
	P280	Wear protective gloves/protective clothing/eye protection/face protection.			
	P284	[In case of inadequate ventilation] wear respiratory protection.			
	P302+P352	IF ON SKIN: Wash with plenty of water.			
	P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.			
	P304+P341	IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.			
	P305+P351+P33 8	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.			
	P308+P313	IF exposed or concerned: Get medical advice/attention.			
	P312	Call a doctor if you feel unwell.			
	P333+P313	If skin irritation or rash occurs: Get medical advice/attention.			
	P337+P313	If eye irritation persists: Get medical advice/attention.			
	P342+P311	If experiencing respiratory symptoms: Call a doctor.			
	P362+P364	Take off contaminated clothing and wash it before reuse.			
	P391	Collect spillage.			
	P403+P233	Store in a well-ventilated place. Keep container tightly closed.			
	P501	Dispose of contents/container in accordance with applicable regulations.			
	. 501	Dispose of contents, container in accordance with applicable regulations.			

Ingredient(s) with unknown acute toxicity:

None

Hazards not otherwise classified identified during the classification process:

None

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances

Not Relevant

Mixtures

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

List of components

Qty	Name	Ident. Numb.	Classification
25-50 %	dibutyl maleate	CAS:105-76-0 EC:203-328-4	STOT RE 2, H373; Aquatic Acute 1, H400; Skin Sens. 1, H317
10-20 %	diphenylmethane-4,4'-diisocyanate	CAS:101-68-8 EC:202-966-0 Index:615-005-00-9	Acute Tox. 4, H332; Eye Irrit. 2A, H319; STOT SE 3, H335; Skin Irrit. 2, H315; Resp. Sens. 1, H334; Skin Sens. 1, H317; STOT RE 2, H373; Carc. 2, H351
5-10 %	4,4'-Methylenediphenyl diisocyanate, oligomers	CAS:25686-28-6 EC:500-040-3	Acute Tox. 4, H332; Eye Irrit. 2A, H319; STOT SE 3, H335; Skin Irrit. 2, H315; Resp. Sens. 1, H334; Skin Sens. 1, H317; STOT RE 2, H373; Carc. 2, H351
0.49-1 %	Reaction mass of 4,4'-methylenediphenyl diisocyanate and o-(p-isocyanatobenzyl)phenyl isocyanate / methylene diphenyl diisocyanate	CAS:26447-40-5 EC:247-714-0 Index:615-005-00-9	Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Resp. Sens. 1, H334; Skin Sens. 1B, H317; Carc. 2, H351; STOT SE 3, H335; STOT RE 2, H373

4. FIRST AID MEASURES

Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Print date 08/26/2025 Production Name RESFOAM HB 45 Page n. 2 of 12

OBTAIN IMMEDIATE MEDICAL ATTENTION.

Obtain medical attention if skin related symptoms persist.

Remove contaminated clothing immediately and dispose of safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an opthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

If breathing is irregular or stopped, administer artificial respiration.

In case of inhalation, consult a doctor immediately and show him packing or label.

Most important symptoms/effects, acute and delayed

Eye irritation

Eye damages

Skin Irritation

Erythema

Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

(see paragraph 4.1)

5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media:

Water.

Carbon dioxide (CO2).

Unsuitable extinguishing media:

None in particular.

Specific hazards arising from the chemical

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products: Not available

Explosive properties: Not available Oxidizing properties: Not available

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Limit leakages with earth or sand.

Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Retain contaminated washing water and dispose it.

7. HANDLING AND STORAGE

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Exercise the greatest care when handling or opening the container.

Do not use on extensive surface areas in premises where there are occupants.

Use localized ventilation system.

Don't use empty container before they have been cleaned.

Print date 08/26/2025 Production Name RESFOAM HB 45 Page n. 3 of 12

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

Conditions for safe storage, including any incompatibilities

Always keep in a well ventilated place.

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

Storage temperature: Not available

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Community Occupational Exposure Limits (OEL)

	OEL Type	Country	Occupational Exposure Limit
diphenylmethane-4,4'- diisocyanate CAS: 101-68-8	ACGIH		Long Term: 0.005 ppm Resp sens
	MAK	GERMANY	Long Term: 0.05 mg/m3
	ACGIH		Long Term: 0.005 ppm respiratory sensitization (listed under Methylene bisphenyl isocyanate (MDI))
	OSHA		Short Term: Ceiling - 0.2 mg/m3 - 0.02 ppm
	MAK	AUSTRIA	Long Term: 0.05 mg/m3 - 0.005 ppm; Short Term: 0.1 mg/m3 - 0.01 ppm
	ACGIH		Long Term: 0.005 ppm respiratory sensitization (listed under Methylene bisphenyl isocyanate (MDI))
	OSHA		Short Term: Ceiling - 0.2 mg/m3 - 0.02 ppm
Reaction mass of 4,4'- methylenediphenyl diisocyanate and o-(p- isocyanatobenzyl)phenyl isocyanate / methylene diphenyl diisocyanate CAS: 26447-40-5	OSHA		Short Term: Ceiling - 0.2 mg/m3 - 0.02 ppm

MAK **AUSTRIA** Short Term: 0.1 mg/m3 - 0.01 ppm

Predicted No Effect Concentration (PNEC) values

diphenylmethane-4,4'diisocyanate

CAS: 101-68-8

Exposure Route: Fresh Water; PNEC Limit: 1 mg/l

Exposure Route: Marine water; PNEC Limit: 0.1 mg/l

Exposure Route: Soil; PNEC Limit: 1 mg/kg

Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 1 mg/l

Exposure Route: Intermittent release; PNEC Limit: 10 mg/l

4,4'-Methylenediphenyl diisocyanate, oligomers

CAS: 25686-28-6

Exposure Route: Fresh Water; PNEC Limit: 1 mg/l

Exposure Route: Marine water; PNEC Limit: 0.1 mg/l

Exposure Route: Soil; PNEC Limit: 1 mg/kg

Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 1 mg/l

Derived No Effect Level (DNEL) values

diphenylmethane-4,4'-

diisocyanate CAS: 101-68-8 Exposure Route: Human Dermal; Exposure Frequency: Short Term, systemic effects

Worker Industry: 50 mg/kg

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects

Worker Industry: 0.1 mg/m3

Print date 08/26/2025 Production Name **RESFOAM HB 45** 4 of 12 Page n.

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, local effects

Worker Industry: 0.1 mg/m3

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects

Worker Industry: 0.05 mg/m3

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects

Worker Industry: 0.05 mg/m3

Exposure Route: Human Dermal; Exposure Frequency: Short Term, systemic effects

Consumer: 25 mg/kg

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects

Consumer: 0.05 mg/m3

Exposure Route: Human Oral; Exposure Frequency: Short Term, systemic effects

Consumer: 20 mg/kg

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, local effects

Consumer: 0.05 mg/m3

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects

Consumer: 0.025 mg/m3

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects

Consumer: 0.025 mg/m3

Exposure Route: Human Dermal; Exposure Frequency: Short Term, local effects

Worker Industry: 28.7 mg/cm2; Consumer: 17.2 mg/cm2

4,4'-Methylenediphenyl diisocyanate, oligomers CAS: 25686-28-6

Exposure Route: Human Dermal; Exposure Frequency: Short Term, systemic effects

Worker Industry: 50 mg/kg; Consumer: 25 mg/kg

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects

Worker Industry: 0.1 mg/m3; Consumer: 0.05 mg/m3

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, local effects

Worker Industry: 0.1 mg/m3; Consumer: 0.05 mg/m3

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects

Worker Industry: 0.05 mg/m3; Consumer: 0.025 mg/m3

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects

Worker Industry: 0.05 mg/m3

Exposure Route: Human Dermal; Exposure Frequency: Short Term, local effects

Worker Industry: 28.7 mg/cm2; Consumer: 17.2 mg/cm2

Exposure Route: Human Oral; Exposure Frequency: Short Term, systemic effects

Consumer: 20 mg/kg

Appropriate engineering controls: Not available

Individual protection measures

Eye protection:

Use close fitting safety goggles, don't use contact lenses.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Suitable materials for safety gloves; 29 CFR 1910.138 - ANSI/ISEA 105:

Polychloroprene - CR: thickness >=0,5mm; breakthrough time >=480min.

Nitrile rubber - NBR: thickness >=0,35mm; breakthrough time >=480min.

Butyl rubber - IIR: thickness >=0,5mm; breakthrough time >=480min.

Fluorinated rubber - FKM: thickness >=0,4mm; breakthrough time >=480min.

Use impervious gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection

Respiratory protection must be used where exposure levels exceed workplace exposure limits. Refer to 29 CFR 1910.134 - CSA Z94.4 for information on selection and use of appropriate respiratory protection equipment.

Use adequate protective respiratory equipment.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state: Liquid

Print date 08/26/2025 Production Name RESFOAM HB 45 Page n. 5 of 12

Appearance and colour: pale yellow

Odour: No data available

Odour threshold: No data available

pH: No data available

Melting point / freezing point: No data available

Initial boiling point and boiling range: No data available

Flash point: 94 °C (201 °F)

Evaporation rate: No data available

Upper/lower flammability or explosive limits: No data available

Vapour density: No data available Vapour pressure: No data available Relative density: 1.05 g/cm3 Solubility in water: Insoluble Solubility in oil: No data available

Partition coefficient (n-octanol/water): No data available

Auto-ignition temperature: No data available Decomposition temperature: No data available

Viscosity: No data available

Explosive properties: No data available Oxidizing properties: No data available Solid/gas flammability: No data available

Other information

Substance Groups relevant properties No data available

Miscibility: No data available Fat Solubility: No data available Conductivity: No data available

10. STABILITY AND REACTIVITY

Reactivity

Stable under normal conditions

Chemical stability

Data not available.

Possibility of hazardous reactions

None.

Conditions to avoid

Stable under normal conditions.

Incompatible materials

None in particular.

Hazardous decomposition products

None.

11. TOXICOLOGICAL INFORMATION

Information on toxicological effects

b) skin corrosion/irritation

c) serious eye damage/irritation

Toxicological Information of the Preparation

a) acute toxicity Not classified

Based on available data, the classification criteria are not met The product is classified: Skin irritation, Category 2(H315)
The product is classified: Eye irritation, Category 2A(H319)

d) respiratory or skin sensitisation The product is classified: Respiratory Sensitization, Category 1(H334), Skin

Sensitization, Category 1(H317)

e) germ cell mutagenicity Not classified

Based on available data, the classification criteria are not met

f) carcinogenicity The product is classified: Carcinogenicity, Category 2(H351)

g) reproductive toxicity Not classified

Based on available data, the classification criteria are not met

h) STOT-single exposure The product is classified: Specific target organ toxicity following single exposure,

Category 3(H335)

i) STOT-repeated exposure The product is classified: Specific target organ toxicity following repeated exposure,

Print date 08/26/2025 Production Name RESFOAM HB 45 Page n. 6 of 12

Category 2(H373)

j) aspiration hazard

Not classified

Based on available data, the classification criteria are not met

Toxicological information on main components of the mixture:

dibutyl maleate

a) acute toxicity

LD50 Oral Rat = 3730 mg/kg

diphenylmethane-4,4'-

diisocyanate

a) acute toxicity

LD50 Oral Rat > 2000 mg/kg

f) carcinogenicity

Carcinogenicity Inhalation Rat = 6 mg/m3

2 y

g) reproductive toxicity

NOAEL Inhalation Rat = 12 mg/m3

20 d

4,4'-Methylenediphenyl diisocyanate, oligomers

a) acute toxicity

LC50 Inhalation Mist Rat 0.368 mg/l 4h

LD50 Skin Rabbit > 9400 mg/kg LD50 Oral Rat > 5000 mg/kg

Reaction mass of 4,4'-

methylenediphenyl diisocyanate and o-(p-isocyanatobenzyl)phenyl isocyanate / methylene diphenyl diisocyanate

a) acute toxicity

LD50 Skin Rabbit > 10000 mg/kg

LC50 Inhalation Rat = 490 mg/m3 4h

LD50 Oral Rat > 10000 mg/kg

Substance(s) listed on the IARC Monographs:

diphenylmethane-4,4'-diisocyanate Group 3

Reaction mass of 4,4'- Group 3 methylenediphenyl diisocyanate and o-(p-isocyanatobenzyl)phenyl isocyanate / methylene diphenyl

diisocyanate

Substance(s) listed as OSHA Carcinogen(s):

None

Substance(s) listed as NIOSH Carcinogen(s):

None

Substance(s) listed on the NTP report on Carcinogens:

None

12. ECOLOGICAL INFORMATION

Toxicity

Adopt good working practices, so that the product is not released into the environment. Eco-Toxicological Information:

List of Eco-Toxicological properties of the product

The product is classified: Acute aquatic hazard, category 1(H400)

List of Eco-Toxicological properties of the components

Component Ident. Numb. Ecotox Data

dibutyl maleate CAS: 105-76-0 - a) Aquatic acute toxicity: EC50 Daphnia Daphnia magna = 21 mg/L 48h

EINECS: 203- IUCLID

328-4

a) Aquatic acute toxicity: EC50 Algae Scenedesmus subspicatus = 6.2 mg/L

72h IUCLID

diphenylmethane-4,4'-diisocyanate CAS: 101-68-8 - a) Aquatic acute toxicity: LC50 Fish > 1000 mg/L 96

EINECS: 202-966-0 - INDEX:

Print date 08/26/2025 Production Name RESFOAM HB 45 Page n. 7 of 12

a) Aquatic acute toxicity: EC50 Daphnia > 1000 mg/L 24

b) Aquatic chronic toxicity: NOEC Daphnia > 10 mg/L - 21 d

a) Aquatic acute toxicity: EC50 Algae > 1640 mg/L 72

c) Bacteria toxicity: EC50 > 100 mg/L 3

d) Terrestrial toxicity: NOEC > 1000 mg/kg - 14 d e) Plant toxicity: NOEC > 1000 mg/kg - 14 d

4,4'-Methylenediphenyl diisocyanate, oligomers

CAS: 25686-28-6 - EINECS: 500-040-3

a) Aquatic acute toxicity: LC50 Fish > 1000 mg/L 96

a) Aquatic acute toxicity: EC50 Algae > 1640 mg/L 72
a) Aquatic acute toxicity: EC50 Daphnia > 1000 mg/L 24
b) Aquatic abrania toxicity: NOCC Daphnia > 10 mg/L 21

b) Aquatic chronic toxicity : NOEC Daphnia > 10 mg/L - 21 d

c) Bacteria toxicity : EC50 Bacteria > 100 mg/L 3 d) Terrestrial toxicity : NOEC > 1000 mg/kg - 14 d e) Plant toxicity : NOEC > 1000 mg/kg - 14 d

Reaction mass of 4,4'methylenediphenyl diisocyanate and o-(p-isocyanatobenzyl)phenyl isocyanate / methylene diphenyl diisocyanate

CAS: 26447-40 5 - EINECS: 247-714-0 -INDEX: 615-

005-00-9

CAS: 26447-40- d) Terrestrial toxicity: LC50 Worm Eisenia foetida > 1000 mg/kg 14d IUCLID

d) Terrestrial toxicity: NOEC Worm Eisenia foetida >= 1000 mg/kg 14d IUCLID

Persistence and degradability

NΑ

Bioaccumulative potential

N.A.

Mobility in soil

N.A.

Other adverse effects

N.A.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

The generation of waste should be avoided or minimized wherever possible. Recover if possible.

Methods of disposal:

Disposal of this product, solutions, packaging and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor.

Do not dispose of waste into sewers.

Disposal considerations:

Do not allow to enter drains or watercourses.

Dispose of product according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions. For further information, contact your local waste authority.

Special precautions:

This material and its container must be disposed of in a safe way. Care should be taken when handling untreated empty containers. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Empty containers or liners may retain some product residues. Do not re-use empty containers.

14. TRANSPORT INFORMATION

UN number

DOT-UN Number: UN3082 ADR-UN number: 3082 IATA-Un number: 3082

Print date 08/26/2025 Production Name RESFOAM HB 45 Page n. 8 of 12

IMDG-Un number: 3082

UN proper shipping name

DOT-Proper Shipping Name: Environmentally hazardous substance, liquid, n.o.s. (dibutyl maleate)

ADR-Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (dibutyl maleate)

IATA-Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (dibutyl maleate)

IMDG-Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (dibutyl maleate)

Transport hazard class(es)

DOT-Hazard Class: 9 ADR-Class: 9 IATA-Class: 9 IMDG-Class: 9

Packing group

DOT Packing Group: III ADR-Packing Group: III IATA-Packing group: III IMDG-Packing group: III

Environmental hazards

Marine pollutant: Yes

Environmental Pollutant: Not Applicable

DOT-RQ: Yes DOT-RQ - Quantity: 5000 lbs

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not Applicable

Special precautions

Department of Transportation (DOT):

DOT-Special Provision(s): 8, 146, 173, 335,441, IB3, T4,

DOT-Label(s): 9
DOT-Symbol: N/A

DOT-Cargo Aircraft: No limit DOT-Passenger Aircraft: No limit

DOT-Bulk: 241 DOT-Non-Bulk: 203

DOT-Limited Quantity threshold: 5 L

Road and Rail (ADR-RID):

ADR-Label: 9

ADR-Hazard identification number: 90

ADR-Transport category (Tunnel restriction code): 3 (-)

Air (IATA):

IATA-Passenger Aircraft: 964 IATA-Cargo Aircraft: 964

IATA-Label: 9

IATA-Subsidiary hazards: -

IATA-Erg: 9L

IATA-Special Provisions: A97 A158 A197 A215

Sea (IMDG):

IMDG-Stowage and handling: Category A

IMDG-Segregation: -IMDG-Subsidiary hazards: -

IMDG-Special Provisions: 274 335 969

IMDG-EMS: F-A, S-F

15. REGULATORY INFORMATION

USA - Federal regulations

TSCA - Toxic Substances Control Act

All the components are listed on the TSCA inventory

TSCA listed substances:

dibutyl maleate is listed in TSCA Section 8b

 $\label{linear} \mbox{diphenylmethane-4,4'-diisocyanate is listed in TSCA} \mbox{ Section 8b Section 8a - PAIR Section 5}$

4,4'-Methylenediphenyl is listed in TSCA Section 8b

diisocyanate, oligomers

Reaction mass of 4,4'- is listed in TSCA Section 8b Section 8a - PAIR Section 5

Print date 08/26/2025 Production Name RESFOAM HB 45 Page n. 9 of 12

methylenediphenyl diisocyanate and o-(p-isocyanatobenzyl)phenyl isocyanate / methylene diphenyl diisocyanate

SARA - Superfund Amendments and Reauthorization Act

Section 302 - Extremely Hazardous Substances:

No substances listed

Section 304 - Hazardous substances:

diphenylmethane-4,4'-diisocyanate

Section 313 - Toxic chemical list:

diphenylmethane-4,4'-diisocyanate

Reaction mass of 4,4'-methylenediphenyl diisocyanate and o-(p-isocyanatobenzyl)phenyl isocyanate / methylene diphenyl diisocyanate

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act Substance(s) listed under CERCLA:

diphenylmethane-4,4'-diisocyanate Reportable quantity: 5000 pounds

CAA - Clean Air Act

CAA listed substances:

diphenylmethane-4,4'-diisocyanate is listed in CAA Section 112(b) - HAP Section 112(b) - HON

CWA - Clean Water Act

CWA listed substances:

No substances listed

USA - State specific regulations

California Proposition 65

Substance(s) listed under California Proposition 65:

No substances listed

Massachusetts Right to know

Substance(s) listed under Massachusetts Right to know:

diphenylmethane-4,4'-diisocyanate

Pennsylvania Right to know

Substance(s) listed under Pennsylvania Right to know:

diphenylmethane-4,4'-diisocyanate

New Jersey Right to know

Substance(s) listed under New Jersey Right to know:

diphenylmethane-4,4'-diisocyanate

Reaction mass of 4,4'-methylenediphenyl diisocyanate and o-(p-isocyanatobenzyl)phenyl isocyanate / methylene diphenyl diisocyanate

Canada - Federal regulations

DSL - Domestic Substances List

All the substances are listed in the DSL.

NDSL - Non Domestic Substances List

This product complies with NDSL inventory

NPRI - National Pollutant Release Inventory

NPRI (National Pollutant Release Inventory) - List of substances listed.

No substances listed

16. OTHER INFORMATION

Safety Data Sheet dated: 12/10/2024 - version 7

Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. The information herein is presented in good faith and believed to be accurate as of the effective date given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or provincial, and local laws.

This document was prepared by a competent person who has received appropriate training.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Print date 08/26/2025 Production Name RESFOAM HB 45 Page n. 10of 12

H373	May cause damage to organs through prolonged or repeated exposure if inhaled.			
H400	Very toxic to aquatic life.			
Code	Hazard class and hazard category	Description		
A.1/4/Inhal	Acute Tox. 4	Acute toxicity (inhalation), Category 4		
A.2/2	Skin Irrit. 2	Skin irritation, Category 2		
A.3/2A	Eye Irrit. 2A	Eye irritation, Category 2A		
A.4.1/1	Resp. Sens. 1	Respiratory Sensitization, Category 1		
A.4.2/1	Skin Sens. 1	Skin Sensitization, Category 1		
A.4.2/1B	Skin Sens. 1B	Skin Sensitization, Category 1B		
A.6/2	Carc. 2	Carcinogenicity, Category 2		
A.8/3	STOT SE 3	Specific target organ toxicity following single exposure, Category 3		
A.9/2	STOT RE 2	Specific target organ toxicity following repeated exposure, Category 2		
US-HAE/A1	Aquatic Acute 1	Acute aquatic hazard, category 1		

Legend to abbreviations and acronyms used in the safety data sheet:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause damage to organs through prolonged or repeated exposure.

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

IMDG: International Maritime Code for Dangerous Goods.

IATA: International Air Transport Association.

Description

Causes skin irritation.

Harmful if inhaled.

May cause an allergic skin reaction.

Causes serious eye irritation.

May cause respiratory irritation.

Suspected of causing cancer.

Code H315

H317

H319

H332

H334

H335 H351

H373

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

CLP: Classification, Labeling, Packaging.

EINECS: European Inventory of Existing Commercial Chemical Substances.

INCI: International Nomenclature of Cosmetic Ingredients.

CAS: Chemical Abstracts Service (division of the American Chemical Society).

 $\label{lem:GefStoffVO:Ordinance} GefStoffVO:\ Ordinance\ on\ Hazardous\ Substances,\ Germany.$

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

DNEL: Derived No Effect Level.

PNEC: Predicted No Effect Concentration.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

STEL: Short Term Exposure limit. STOT: Specific Target Organ Toxicity. WGK: German Water Hazard Class.

KSt: Explosion coefficient.

Paragraphs modified from the previous revision:

- 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING
- 2. HAZARDS IDENTIFICATION
- 3. COMPOSITION/INFORMATION ON INGREDIENTS
- 5. FIRE-FIGHTING MEASURES
- 7. HANDLING AND STORAGE
- 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
- 9. PHYSICAL AND CHEMICAL PROPERTIES
- 11. TOXICOLOGICAL INFORMATION
- 12. ECOLOGICAL INFORMATION
- 14. TRANSPORT INFORMATION

Print date 08/26/2025 Production Name RESFOAM HB 45 Page n. 11of 12

- 15. REGULATORY INFORMATION
- 16. OTHER INFORMATION

Print date 08/26/2025 Production Name RESFOAM HB 45 Page n. 12 of 12