Safety Data Sheet

MAPEFLEX JOINT FILLER EP 90/50 / A

Safety Data Sheet dated: 01/31/2025 - version 4

Date of first edition: 06/16/2021



1. IDENTIFICATION

Product identifier used on the label

Mixture identification:

Trade name: MAPEFLEX JOINT FILLER EP 90/50 / A

Trade code: 902UR9990

Recommended use of the chemical and restrictions on use

Recommended use: Epoxy resins Restrictions on use: Not available

Name, U.S. address, and U.S. telephone number of the chemical manufacturer, importer, or other responsible party

Company: MAPEI CORP. (USA and Puerto Rico)

1144 East Newport Center Drive - 33442 - Deerfield Beach - FL - USA

Phone: 954-246-8888

Responsable: RDProductSafety@mapei.com

Emergency 24 hour numbers:

Emergency Number (USA/Canada) CHEMTREC 1(800) 424-9300 / 1(703) 527-3887

Emergency Transport CANUTEC (Canada) 1-613-996-6666

2. HAZARD(S) IDENTIFICATION









Classification of the chemical

Skin irritation, Category 2 Causes skin irritation.

Serious eye damage, Category 1 Causes serious eye damage.

Skin Sensitization, Category 1A May cause an allergic skin reaction.

Reproductive toxicity, Category 1B May damage fertility. May damage the unborn child.

Acute aquatic hazard, category 2 Toxic to aquatic life

Chronic (long term) aquatic hazard, category 2 Toxic to aquatic life with long lasting effects.

Label elements

Hazard pictograms and Signal Word



Danger

Hazard statements

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H360FD May damage fertility. May damage the unborn child.

H401 Toxic to aquatic life

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P261 Avoid breathing mist/vapours/spray.
P264 Wash skin thoroughly after handling.
P273 Avoid release to the environment.

P280 Wear protective gloves and eye/face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

Print date 07/22/2025 Production Name MAPEFLEX JOINT FILLER EP 90/50 / A Page n. 1 of 11

P305+P351+P33 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P310 Immediately call a doctor.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.

P391 Collect spillage.

P501 Dispose of contents/container in accordance with applicable regulations.

Ingredient(s) with unknown acute toxicity:

None

Hazards not otherwise classified identified during the classification process:

None

This product contains titanium dioxide which IARC has classified as a Group 2B carcinogen (possibly carcinogenic to humans). Evidence is based on sufficient animal testing as a result of long-term inhalation at high concentrations of respirable amounts of titanium dioxide. Because this product is in liquid or paste form, it does not pose a dust hazard; therefore, this classification is not relevant. (Note: sanding of the hardened product may create a dust hazard)

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances

Not Relevant

Mixtures

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

List of components

Qty	Name	Ident. Numb.	Classification	
50-75 %	bis-[4-(2,3-epoxipropoxi)phenyl]propane	CAS:1675-54-3, 25085- 99-8 EC:216-823-5 Index:603-073-00-2	Skin Irrit. 2, H315; Skin Sens. 1, H317; Eye Irrit. 2A, H319; Aquatic Chronic 2, H411; Aquatic Acute 2, H401	
5-10 %	Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and pheno		Skin Irrit. 2, H315; Aquatic Chronic 2, H411; Skin Sens. 1, H317	
5-10 %	oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	CAS:68609-97-2 EC:271-846-8 Index:603-103-00-4	Skin Irrit. 2, H315; Skin Sens. 1B, H317; Repr. 1B, H360F	
2.5-5 %		CAS:8007-24-7 EC:232-355-4	Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Irrit. 2, H315; Eye Dam. 1, H318; Skin Sens. 1A, H317	
1-2.5 %	titanium dioxide	CAS:13463-67-7 EC:236-675-5 Index:022-006-00-2	Carc. 2, H351	

4. FIRST AID MEASURES

Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

OBTAIN IMMEDIATE MEDICAL ATTENTION.

Obtain medical attention if skin related symptoms persist.

Remove contaminated clothing immediately and dispose of safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an opthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

Most important symptoms/effects, acute and delayed

Eye irritation

Print date 07/22/2025 Production Name MAPEFLEX JOINT FILLER EP 90/50 / A Page n. 2 of 11

Erythema

Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

(see paragraph 4.1)

5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media:

Water.

Carbon dioxide (CO2).

Unsuitable extinguishing media:

None in particular.

Specific hazards arising from the chemical

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products: Not available

Explosive properties: Not Relevant Oxidizing properties: Not Relevant

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove persons to safety.

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Limit leakages with earth or sand.

Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Retain contaminated washing water and dispose it.

7. HANDLING AND STORAGE

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Exercise the greatest care when handling or opening the container.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

Conditions for safe storage, including any incompatibilities

Store cool and dry.

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

Storage temperature: Not available

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Community Occupational Exposure Limits (OEL)

OEL Country **Occupational Exposure Limit**

Type

Print date

07/22/2025

Production Name

MAPEFLEX JOINT FILLER EP 90/50 / A

Page n.

titanium dioxide CAS: 13463-67-7 ACGIH Long Term: 10 mg/m3

A4 - LRT irr

MAK GERMANY Long Term: 0.3 mg/m3
OSHA Long Term: 15 mg/m3
ACGIH Long Term: 10 mg/m3

A4 - Not Classifiable as a Human Carcinogen; lower respiratory tract irritation

MAK AUSTRIA Long Term: 5 mg/m3; Short Term: 10 mg/m3

MAK SWITZERLAN Long Term: 3 mg/m3

D

Predicted No Effect Concentration (PNEC) values

Formaldehyde, oligomeric Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 10 mg/l

reaction products with 1-chloro-2,3-epoxypropane

and phenol CAS: 9003-36-5

Exposure Route: Fresh Water; PNEC Limit: 0.003 mg/l

Exposure Route: Freshwater sediments; PNEC Limit: 0.294 mg/kg

Exposure Route: Marine water; PNEC Limit: 0.0003 mg/l

Exposure Route: Marine water sediments; PNEC Limit: 0.0294 mg/kg

Exposure Route: Soil; PNEC Limit: 0.237 mg/kg

oxirane, mono[(C12-14-

Exposure Route: Marine water; PNEC Limit: 0.00072 mg/l

alkyloxy)methyl] derivs. CAS: 68609-97-2

Exposure Route: Fresh Water; PNEC Limit: 0.0072 mg/l

Exposure Route: Freshwater sediments; PNEC Limit: 66.77 mg/kg Exposure Route: Marine water sediments; PNEC Limit: 6.677 mg/kg

Exposure Route: Soil; PNEC Limit: 80.12 mg/kg

Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 10 mg/l

titanium dioxide CAS: 13463-67-7

Exposure Route: Soil; PNEC Limit: 100 mg/kg

Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 100 mg/l

Exposure Route: Marine water; PNEC Limit: 0.0184 mg/l

Exposure Route: Fresh Water; PNEC Limit: 0.184 mg/l

Exposure Route: Marine water sediments; PNEC Limit: 100 mg/kg Exposure Route: Freshwater sediments; PNEC Limit: 1000 mg/kg Exposure Route: Intermittent release; PNEC Limit: 0.193 mg/l

Derived No Effect Level (DNEL) values

titanium dioxide Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects

CAS: 13463-67-7 Worker Industry: 0.17 mg/m3

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects

Consumer: 0.028 mg/m3

Appropriate engineering controls: Not available

Individual protection measures

Eye protection:

Use close fitting safety goggles, don't use contact lenses.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Suitable materials for safety gloves; 29 CFR 1910.138 - ANSI/ISEA 105:

Polychloroprene - CR: thickness >=0,5mm; breakthrough time >=480min.

Nitrile rubber - NBR: thickness >=0,35mm; breakthrough time >=480min.

Butyl rubber - IIR: thickness >=0,5mm; breakthrough time >=480min.

Fluorinated rubber - FKM: thickness >=0,4mm; breakthrough time >=480min.

Use impervious gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Respiratory protection must be used where exposure levels exceed workplace exposure limits. Refer to 29 CFR 1910.134 - CSA

Print date 07/22/2025 Production Name MAPEFLEX JOINT FILLER EP 90/50 / A Page n. 4 of 11

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state: Liquid

Appearance and colour: liquid various

Odour: Characteristic

Odour threshold: Not Relevant

pH: Not Relevant

Melting point / freezing point: Not Relevant
Initial boiling point and boiling range: Not Relevant

Flash point: 94 °C (201 °F) Evaporation rate: Not Relevant

Upper/lower flammability or explosive limits: Not Relevant

Vapour density: Not Relevant Vapour pressure: Not Relevant Relative density: 1.17 g/cm3 Solubility in water: Insoluble Solubility in oil: insoluble

Partition coefficient (n-octanol/water): Not Relevant

Auto-ignition temperature: Not Relevant Decomposition temperature: Not Relevant

Viscosity: 36,600.00 cPs

Kinematic viscosity: > 20,5 mm2/sec (40 °C) mm2/s

Explosive properties: Not Relevant Oxidizing properties: Not Relevant Solid/gas flammability: Not Relevant

Other information

Substance Groups relevant properties Not Relevant

Miscibility: Not Relevant Fat Solubility: Not Relevant Conductivity: Not Relevant

10. STABILITY AND REACTIVITY

Reactivity

Stable

Chemical stability

Data not available.

Possibility of hazardous reactions

It may catch fire on contact with powerful oxidising agents.

Conditions to avoid

No data available

Incompatible materials

Data not available.

Hazardous decomposition products

Data not available.

11. TOXICOLOGICAL INFORMATION

Information on toxicological effects

Toxicological Information of the Preparation

a) acute toxicity Not classified

Based on available data, the classification criteria are not met

b) skin corrosion/irritation The product is classified: Skin irritation, Category 2(H315)

c) serious eye damage/irritation The product is classified: Serious eye damage, Category 1(H318) d) respiratory or skin sensitisation The product is classified: Skin Sensitization, Category 1A(H317)

e) germ cell mutagenicity Not classified

Based on available data, the classification criteria are not met

f) carcinogenicity Not classified

Based on available data, the classification criteria are not met

Print date 07/22/2025 Production Name MAPEFLEX JOINT FILLER EP 90/50 / A Page n. 5 of 11

The product is classified: Reproductive toxicity, Category 1B(H360) g) reproductive toxicity

h) STOT-single exposure Not classified

Based on available data, the classification criteria are not met

i) STOT-repeated exposure Not classified

Based on available data, the classification criteria are not met

j) aspiration hazard Not classified

Based on available data, the classification criteria are not met

Toxicological information on main components of the mixture: a) acute toxicity

bis-[4-(2,3epoxipropoxi)phenyl]

propane

LD50 Skin Rabbit = 20 mg/kg

LD50 Oral Rat = $11300 \mu L/kg$

Formaldehyde, oligomeric a) acute toxicity

reaction products with 1chloro-2,3-epoxypropane and phenol

LD50 Oral Rat > 5000 mg/kg

i) STOT-repeated

exposure

NOAEL Oral = 250 mg/kg

oxirane, mono[(C12-14- a) acute toxicity

alkyloxy)methyl] derivs.

LD50 Oral Rat = 19200 mg/kg

LD50 Skin Rat > 2000 mg/kg

LD50 Skin Rabbit = 4000 mg/kg

a) acute toxicity

LD50 Oral Rat > 1000 mg/kg

titanium dioxide

a) acute toxicity

LD50 Oral Rat > 5000 mg/kg LD50 Skin Rat > 2000 mg/m3

LC50 Inhalation Dust Rat > 6.82 mg/l 4h

LD50 Skin Rabbit > 10000 mg/kg

Substance(s) listed on the IARC Monographs:

Group 3 bis-[4-(2,3-

epoxipropoxi)phenyl]propane

titanium dioxide Group 2B

Substance(s) listed as OSHA Carcinogen(s):

titanium dioxide

Substance(s) listed as NIOSH Carcinogen(s):

titanium dioxide

Substance(s) listed on the NTP report on Carcinogens:

None

12. ECOLOGICAL INFORMATION

Toxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

List of Eco-Toxicological properties of the product

The product is classified: Acute aquatic hazard, category 2(H401), Chronic (long term) aquatic hazard, category 2(H411)

List of Eco-Toxicological properties of the components

Component Ident. Numb. **Ecotox Data**

Print date 07/22/2025 MAPEFLEX JOINT FILLER EP 90/50 / A 6 of 11 Production Name Page n.

bis-[4-(2,3- CAS: 1675-54-3, a) Aquatic acute toxicity: LC50 Fish = 2 mg/L 96h

epoxipropoxi)phenyl]propane

25085-99-8 -EINECS: 216-823-5 - INDEX: 603-073-00-2

a) Aquatic acute toxicity: EC50 Daphnia = 1.8 mg/L 48h

Formaldehyde, oligomeric reaction CAS: 9003-36-5 a) Aquatic acute toxicity: LC50 Fish = 5.7 mg/L 96h

products with 1-chloro-2,3-

- EINECS: 701-

epoxypropane and phenol 263-0

a) Aquatic acute toxicity : EC50 Daphnia = 2.55 mg/L 48 h

a) Aquatic acute toxicity: EC50 Algae = 1.8 mg/L 72h

oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

2 - EINECS:

CAS: 68609-97- a) Aquatic acute toxicity: LC50 Fish > 100 mg/L 96h

271-846-8 -INDEX: 603-103-00-4

a) Aquatic acute toxicity: EL50 Daphnia = 7.2 mg/L 48h
 a) Aquatic acute toxicity: EC50 Algae = 843 mg/L 72h

b) Aquatic chronic toxicity: NOEC Algae = 500 mg/L 72h

titanium dioxide CAS: 13463-67

7 - EINECS: 236-675-5 -INDEX: 022-006-00-2

CAS: 13463-67- a) Aquatic acute toxicity : LC50 Fish > 100 mg/L 96

a) Aquatic acute toxicity: EC50 Algae = 16 mg/L 72
 a) Aquatic acute toxicity: NOEC Algae = 5600 mg/L 72
 a) Aquatic acute toxicity: EC50 Daphnia > 100 mg/L 48

Persistence and degradability

Component Persitence/Degradability:

oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

Readily biodegradable

Bioaccumulative potential

Component Bioaccumulation

oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

Not bioaccumulative

Mobility in soil

N.A.

Other adverse effects

N.A.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

The generation of waste should be avoided or minimized wherever possible. Recover if possible.

Methods of disposal:

Disposal of this product, solutions, packaging and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor.

Do not dispose of waste into sewers.

Disposal considerations:

Do not allow to enter drains or watercourses.

Dispose of product according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions. For further information, contact your local waste authority.

Special precautions:

This material and its container must be disposed of in a safe way. Care should be taken when handling untreated empty containers. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Empty containers or liners may retain some product residues. Do not re-use empty containers.

Print date 07/22/2025 Production Name MAPEFLEX JOINT FILLER EP 90/50 / A Page n. 7 of 11

14. TRANSPORT INFORMATION

UN number

DOT-UN Number: UN3082 ADR-UN number: 3082 IATA-Un number: 3082 IMDG-Un number: 3082

UN proper shipping name

DOT-Proper Shipping Name: Environmentally hazardous substance, liquid, n.o.s. (epoxy resins)

ADR-Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxy resins)

IATA-Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxy resins)

IMDG-Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxy resins)

Transport hazard class(es)

DOT-Hazard Class: 9 ADR-Class: 9 IATA-Class: 9 IMDG-Class: 9

Packing group

DOT Packing Group: III ADR-Packing Group: III IATA-Packing group: III IMDG-Packing group: III

Environmental hazards

Marine pollutant: Yes

Environmental Pollutant: Not Applicable

DOT-RQ: No

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not Applicable

Special precautions

Department of Transportation (DOT):

DOT-Special Provision(s): 8, 146, 173, 335, IB3, T4, TP1, TP29

DOT-Label(s): 9 DOT-Symbol: N/A DOT-Cargo Aircraft: N/A DOT-Passenger Aircraft: N/A

DOT-Bulk: N/A DOT-Non-Bulk: N/A

DOT-Limited Quantity threshold: 5 L

Road and Rail (ADR-RID):

ADR-Label: 9

ADR-Hazard identification number: 90

ADR-Transport category (Tunnel restriction code): 3 (-)

Air (IATA):

IATA-Passenger Aircraft: 964 IATA-Cargo Aircraft: 964

IATA-Label: 9

IATA-Subsidiary hazards: -

IATA-Erg: 9L

IATA-Special Provisions: A97 A158 A197

Sea (IMDG):

IMDG-Stowage and handling: Category A

IMDG-Segregation: -IMDG-Subsidiary hazards: -

IMDG-Special Provisions: 274 335 969

IMDG-EMS: F-A, S-F

15. REGULATORY INFORMATION

USA - Federal regulations

TSCA - Toxic Substances Control Act

All the components are listed on the TSCA inventory

TSCA listed substances:

Print date 07/22/2025 Production Name MAPEFLEX JOINT FILLER EP 90/50 / A Page n. 8 of 11

bis-[4-(2,3- is listed in TSCA Section 8b

epoxipropoxi)phenyl]propane

Formaldehyde, oligomeric reaction is listed in TSCA Section 8b

products with 1-chloro-2,3-epoxypropane and phenol

oxirane, mono[(C12-14- is listed in TSCA Section 8b

alkyloxy)methyl] derivs.

is listed in TSCA Section 8b

titanium dioxide is listed in TSCA Section 8b

SARA - Superfund Amendments and Reauthorization Act

Section 302 - Extremely Hazardous Substances:

No substances listed

Section 304 - Hazardous substances:

No substances listed

Section 313 - Toxic chemical list:

No substances listed

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

Substance(s) listed under CERCLA:

No substances listed

CAA - Clean Air Act

CAA listed substances:

No substances listed

CWA - Clean Water Act

CWA listed substances:

No substances listed

USA - State specific regulations

California Proposition 65

Substance(s) listed under California Proposition 65:

titanium dioxide Listed as carcinogen

Massachusetts Right to know

Substance(s) listed under Massachusetts Right to know:

titanium dioxide

Pennsylvania Right to know

Substance(s) listed under Pennsylvania Right to know:

titanium dioxide

New Jersey Right to know

Substance(s) listed under New Jersey Right to know:

titanium dioxide

Canada - Federal regulations

DSL - Domestic Substances List

All the substances are listed in the DSL.

NDSL - Non Domestic Substances List

This product complies with NDSL inventory

NPRI - National Pollutant Release Inventory

NPRI (National Pollutant Release Inventory) - List of substances listed.

No substances listed

16. OTHER INFORMATION

Safety Data Sheet dated: 1/31/2025 - version 4

Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. The information herein is presented in good faith and believed to be accurate as of the effective date given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or provincial, and local laws.

This document was prepared by a competent person who has received appropriate training.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

Print date 07/22/2025 Production Name MAPEFLEX JOINT FILLER EP 90/50 / A Page n. 9 of 11

This SDS cancels and replaces any preceding release.

Code	Description
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H351	Suspected of causing cancer.
H360F	May damage fertility.
H401	Toxic to aquatic life
H411	Toxic to aquatic life with long lasting effects.

Code	Hazard class and hazard category	Description
A.1/4/Dermal	Acute Tox. 4	Acute toxicity (dermal), Category 4
A.1/4/Oral	Acute Tox. 4	Acute toxicity (oral), Category 4
A.2/2	Skin Irrit. 2	Skin irritation, Category 2
A.3/1	Eye Dam. 1	Serious eye damage, Category 1
A.3/2A	Eye Irrit. 2A	Eye irritation, Category 2A
A.4.2/1	Skin Sens. 1	Skin Sensitization, Category 1
A.4.2/1A	Skin Sens. 1A	Skin Sensitization, Category 1A
A.4.2/1B	Skin Sens. 1B	Skin Sensitization, Category 1B
A.6/2	Carc. 2	Carcinogenicity, Category 2
A.7/1B	Repr. 1B	Reproductive toxicity, Category 1B
US-HAE/A2	Aquatic Acute 2	Acute aquatic hazard, category 2
US-HAE/C2	Aquatic Chronic 2	Chronic (long term) aquatic hazard, category 2

Legend to abbreviations and acronyms used in the safety data sheet:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

IMDG: International Maritime Code for Dangerous Goods.

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

CLP: Classification, Labeling, Packaging.

EINECS: European Inventory of Existing Commercial Chemical Substances.

INCI: International Nomenclature of Cosmetic Ingredients.

CAS: Chemical Abstracts Service (division of the American Chemical Society).

GefStoffVO: Ordinance on Hazardous Substances, Germany. LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

DNEL: Derived No Effect Level.

PNEC: Predicted No Effect Concentration.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

STEL: Short Term Exposure limit. STOT: Specific Target Organ Toxicity. WGK: German Water Hazard Class.

KSt: Explosion coefficient.

Paragraphs modified from the previous revision:

- 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING
- 2. HAZARDS IDENTIFICATION
- 3. COMPOSITION/INFORMATION ON INGREDIENTS
- 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
- 9. PHYSICAL AND CHEMICAL PROPERTIES
- 11. TOXICOLOGICAL INFORMATION
- 12. ECOLOGICAL INFORMATION

Print date 07/22/2025 Production Name MAPEFLEX JOINT FILLER EP 90/50 / A Page n. 10of 11

- 15. REGULATORY INFORMATION
- 16. OTHER INFORMATION

Print date 07/22/2025 Production Name MAPEFLEX JOINT FILLER EP 90/50 / A Page n. 11 of 11