Safety Data Sheet ELASTOCOLOR PRIMER AR

Safety Data Sheet dated: 04/21/2025 - version 5

Date of first edition: 11/29/2017



1. IDENTIFICATION

Product identifier

Mixture identification:

Trade name: ELASTOCOLOR PRIMER AR

Trade code: 907UH9990

Recommended use of the chemical and restrictions on use

Recommended use: Coating Restrictions on use: Not available

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Company: MAPEI CORP. (USA and Puerto Rico)

1144 East Newport Center Drive - 33442 - Deerfield Beach - FL - USA

Phone: 954-246-8888

Responsable: RDProductSafety@mapei.com

Emergency 24 hour numbers:

Emergency Number (USA/Canada) CHEMTREC 1(800) 424-9300 / 1(703) 527-3887

Emergency Transport CANUTEC (Canada) 1-613-996-6666

2. HAZARD(S) IDENTIFICATION





Classification of the chemical

Skin Sensitization, Category 1 May cause an allergic skin reaction.

Germ cell mutagenicity, Category 1B May cause genetic defects if inhaled, in contact with skin and if

swallowed.

Reproductive toxicity, Category 1B May damage fertility. May damage the unborn child.

Acute aquatic hazard, category 3 Harmful to aquatic life

Chronic (long term) aquatic hazard, category 3 Harmful to aquatic life with long lasting effects.

Label elements

Hazard pictograms and Signal Word



Danger

Hazard statements

H317 May cause an allergic skin reaction.

H340 May cause genetic defects if inhaled, in contact with skin and if swallowed.

H360FD May damage fertility. May damage the unborn child.

H402 Harmful to aquatic life

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P261 Avoid breathing mist/vapours/spray. P273 Avoid release to the environment.

P280 Wear protective gloves/clothing and eye/face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P308+P313 IF exposed or concerned: Get medical advice/attention.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

Print date 05/22/2025 Production Name ELASTOCOLOR PRIMER AR Page n. 1 of 10

Ingredient(s) with unknown acute toxicity:

None

Hazards not otherwise classified identified during the classification process:

None

This product contains crystalline silica (quartz sand). IARC has classified crystalline silica as a Group 1 carcinogen. Both IARC and NTP consider silica as a known human carcinogen. Evidence is based on the chronic and long-term exposure workers have had to respirable sized crystalline silica dust particles. Because this product is in liquid or paste form, it does not pose a dust hazard; therefore, this classification is not relevant. (Note: sanding of the hardened product may create a silica dust hazard)

This product contains titanium dioxide which IARC has classified as a Group 2B carcinogen (possibly carcinogenic to humans). Evidence is based on sufficient animal testing as a result of long-term inhalation at high concentrations of respirable amounts of titanium dioxide. Because this product is in liquid or paste form, it does not pose a dust hazard; therefore, this classification is not relevant. (Note: sanding of the hardened product may create a dust hazard)

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances

Not Relevant

Mixtures

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

List of components

| Qty | Name | Ident. Numb. | Classification |
|-------------|--|--|--|
| 5-10 % | titanium dioxide | CAS:13463-67-7 EC:236-675-5 Index:022-006-00-2 | Carc. 2, H351 |
| 0.25-0.49 % | polyethylene glycol monooleylether | CAS:9004-98-2 EC:500-016-2 | Skin Irrit. 2, H315; Aquatic Acute 1, H400 |
| 0.1-0.25 % | free crystalline silica (Ø >10 μ) | CAS:14808-60-7 EC:238-878-4 | STOT RE 1, H372; Carc. 1A, H350 |
| 0.1-0.25 % | carbendazim (ISO); methyl benzimidazol- 2-ylcarbamate | CAS:10605-21-7 EC:234-232-0 Index:613-048-00-8 | Muta. 1B, H340; Repr. 1B, H360FD; Skin Sens. 1, H317; Aquatic Acute 1, H400; Aquatic Chronic 1, H410 |

4. FIRST AID MEASURES

Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

OBTAIN IMMEDIATE MEDICAL ATTENTION.

Obtain medical attention if skin related symptoms persist.

Remove contaminated clothing immediately and dispose of safely.

In case of eyes contact:

Wash immediately with water.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

Most important symptoms/effects, acute and delayed

Not available

Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

(see paragraph 4.1)

5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media:

Water.

Carbon dioxide (CO2).

Unsuitable extinguishing media:

Print date 05/22/2025 Production Name ELASTOCOLOR PRIMER AR Page n. 2 of 10

None in particular.

Specific hazards arising from the chemical

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products: Not available

Explosive properties: Not available Oxidizing properties: Not available

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove persons to safety.

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Limit leakages with earth or sand.

Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Retain contaminated washing water and dispose it.

7. HANDLING AND STORAGE

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Exercise the greatest care when handling or opening the container.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

Conditions for safe storage, including any incompatibilities

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

Storage temperature: Not available

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

| Community Occupational Exposure Limits (OEL) | | | | | |
|--|-------------|-----------------|---|--|--|
| | OEL Type | Country | Occupational Exposure Limit | | |
| titanium dioxide CAS: 13463-67-7 | ACGIH | | Long Term: 10 mg/m3 A4 - LRT irr | | |
| | MAK | GERMANY | Long Term: 0.3 mg/m3 | | |
| | OSHA | | Long Term: 15 mg/m3 | | |
| | ACGIH | | Long Term: 10 mg/m3 A4 - Not Classifiable as a Human Carcinogen;lower respiratory tract irritation | | |
| | MAK | AUSTRIA | Long Term: 5 mg/m3; Short Term: 10 mg/m3 | | |
| | MAK | SWITZERLAN D | Long Term: 3 mg/m3 | | |
| free crystalline silica (Ø >10 μ) CAS: 14808-60-7 | ACGIH | | Long Term: 0.025 mg/m3 A2 - Suspected Human Carcinogen;lung cancer;pulmonary fibrosis | | |
| | MAK | AUSTRIA | Long Term: 0.15 mg/m3 | | |
| | ACGIH | | Long Term: 0.025 mg/m3 | | |

Print date 05/22/2025 Production Name **ELASTOCOLOR PRIMER AR** 3 of 10 Page n.

(R), A2 - Pulm fibrosis, lung cancer

MAK SWITZERLAN Long Term: 0.15 mg/m3

FU Long Term: 0.1 mg/m3

Behaviour Binding

carbendazim (ISO); methyl MAK

benzimidazol-2-ylcarbamate

CAS: 10605-21-7

GERMANY Long Term: 10 mg/m3

MAK SWITZERLAN Long Term: 10 mg/m3

Predicted No Effect Concentration (PNEC) values

titanium dioxide

Exposure Route: Fresh Water; PNEC Limit: 0.184 mg/l

CAS: 13463-67-7

Exposure Route: Soil; PNEC Limit: 100 mg/kg

Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 100 mg/l

Exposure Route: Marine water; PNEC Limit: 0.0184 mg/l

Exposure Route: Marine water sediments; PNEC Limit: 100 mg/kg Exposure Route: Freshwater sediments; PNEC Limit: 1000 mg/kg Exposure Route: Intermittent release; PNEC Limit: 0.193 mg/l

Derived No Effect Level (DNEL) values

titanium dioxide Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects

CAS: 13463-67-7 Worker Industry: 0.17 mg/m3

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects

Consumer: 0.028 mg/m3

Appropriate engineering controls: Not available

Individual protection measures

Eye protection:

Use close fitting safety goggles, don't use contact lenses.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Suitable materials for safety gloves; 29 CFR 1910.138 - ANSI/ISEA 105:

Polychloroprene - CR: thickness >=0,5mm; breakthrough time >=480min.

Nitrile rubber - NBR: thickness >=0,35mm; breakthrough time >=480min.

Butyl rubber - IIR: thickness >=0,5mm; breakthrough time >=480min.

Fluorinated rubber - FKM: thickness >=0,4mm; breakthrough time >=480min.

Use impervious gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Respiratory protection must be used where exposure levels exceed workplace exposure limits. Refer to 29 CFR 1910.134 - CSA Z94.4 for information on selection and use of appropriate respiratory protection equipment.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state: Liquid

Appearance and colour: liquid white

Odour: ammonia

Odour threshold: No data available

pH: 9.25

Melting point / freezing point: No data available

Initial boiling point and boiling range: No data available

Flash point: 100 °C (212 °F) Evaporation rate: No data available

Upper/lower flammability or explosive limits: No data available

Vapour density: No data available Vapour pressure: No data available Relative density: 1.31 g/cm3 Solubility in water: easily soluble

Print date 05/22/2025 Production Name **ELASTOCOLOR PRIMER AR** 4 of 10 Page n.

Solubility in oil: No data available

Partition coefficient (n-octanol/water): No data available

Auto-ignition temperature: No data available Decomposition temperature: No data available

Viscosity: No data available

Kinematic viscosity: <= 20,5 mm2/sec (40 °C) mm2/s

Explosive properties: No data available Oxidizing properties: No data available Solid/gas flammability: No data available

Other information

Substance Groups relevant properties No data available

Miscibility: No data available Fat Solubility: No data available Conductivity: No data available

10. STABILITY AND REACTIVITY

Reactivity

Stable under normal conditions

Chemical stability

Data not available.

Possibility of hazardous reactions

None.

Conditions to avoid

Stable under normal conditions.

Incompatible materials

None in particular.

Hazardous decomposition products

None.

11. TOXICOLOGICAL INFORMATION

Information on toxicological effects

Toxicological Information of the Preparation

a) acute toxicity

Not classified

Based on available data, the classification criteria are not met

Based on available data, the classification criteria are not met

c) serious eye damage/irritation Not classified

Based on available data, the classification criteria are not met

d) respiratory or skin sensitisation The product is classified: Skin Sensitization, Category 1(H317)

e) germ cell mutagenicity The product is classified: Germ cell mutagenicity, Category 1B(H340)

f) carcinogenicity Not classified

Based on available data, the classification criteria are not met

g) reproductive toxicity The product is classified: Reproductive toxicity, Category 1B(H360)

h) STOT-single exposure Not classified

Based on available data, the classification criteria are not met

i) STOT-repeated exposure Not classified

Based on available data, the classification criteria are not met

j) aspiration hazard Not classified

Based on available data, the classification criteria are not met

Toxicological information on main components of the mixture:

titanium dioxide a) acute toxicity LD50 Oral Rat > 5000 mg/kg

LD50 Skin Rat > 2000 mg/m3

LC50 Inhalation Dust Rat > 6.82 mg/l 4h

LD50 Skin Rabbit > 10000 mg/kg

polyethylene glycol

monooleylether

a) acute toxicity LD50 Oral Rat 2700 mg/kg

Print date 05/22/2025 Production Name ELASTOCOLOR PRIMER AR Page n. 5 of 10

LD50 Oral Rat = 2700 mg/kg

free crystalline silica (Ø

a) acute toxicity

LD50 Oral > 2000 mg/kg

 $>10 \mu$)

LD50 Skin > 2000 mg/kg

carbendazim (ISO);

methyl benzimidazol-2ylcarbamate

a) acute toxicity

LD50 Skin Rabbit > 10000 mg/kg

LD50 Oral Rat > 5050 mg/kg

LD50 Skin Rabbit > 10000 mg/kg

Substance(s) listed on the IARC Monographs:

titanium dioxide

Group 2B

free crystalline silica ($\emptyset > 10 \mu$)

Group 1

Substance(s) listed as OSHA Carcinogen(s):

titanium dioxide

free crystalline silica ($\emptyset > 10 \mu$)

Substance(s) listed as NIOSH Carcinogen(s):

titanium dioxide

free crystalline silica ($\emptyset > 10 \mu$)

Substance(s) listed on the NTP report on Carcinogens:

free crystalline silica ($\emptyset > 10 \mu$)

12. ECOLOGICAL INFORMATION

Toxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

List of Eco-Toxicological properties of the product

The product is classified: Acute aquatic hazard, category 3(H402), Chronic (long term) aquatic hazard, category 3(H412)

List of Eco-Toxicological properties of the components

Component

Ident. Numb. Ecotox Data

titanium dioxide

7 - EINECS: 236-675-5 -INDEX: 022-

006-00-2

CAS: 13463-67- a) Aquatic acute toxicity: LC50 Fish > 100 mg/L 96

a) Aquatic acute toxicity: EC50 Algae = 16 mg/L 72 a) Aquatic acute toxicity : NOEC Algae = 5600 mg/L 72a) Aquatic acute toxicity: EC50 Daphnia > 100 mg/L 48

Persistence and degradability

N.A.

Bioaccumulative potential

N.A.

Mobility in soil

N.A.

Other adverse effects

N.A.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Print date 05/22/2025 Production Name **ELASTOCOLOR PRIMER AR** Page n. 6 of 10 The generation of waste should be avoided or minimized wherever possible. Recover if possible.

Methods of disposal:

Disposal of this product, solutions, packaging and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor.

Do not dispose of waste into sewers.

Disposal considerations:

Do not allow to enter drains or watercourses.

Dispose of product according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions. For further information, contact your local waste authority.

Special precautions:

This material and its container must be disposed of in a safe way. Care should be taken when handling untreated empty containers.

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Empty containers or liners may retain some product residues. Do not re-use empty containers.

14. TRANSPORT INFORMATION

Not classified as dangerous in the meaning of transport regulations.

UN number

DOT-UN Number: Not Applicable ADR-UN number: Not Applicable IATA-Un number: Not Applicable IMDG-Un number: Not Applicable

UN proper shipping name

DOT-Proper Shipping Name: Not Applicable

ADR-Shipping Name: Not Applicable IATA-Technical name: Not Applicable IMDG-Technical name: Not Applicable

Transport hazard class(es)

DOT-Hazard Class: Not Applicable

ADR-Class: Not Applicable IATA-Class: Not Applicable IMDG-Class: Not Applicable

Packing group

DOT Packing Group: Not Applicable ADR-Packing Group: Not Applicable IATA-Packing group: Not Applicable IMDG-Packing group: Not Applicable

Environmental hazards

Marine pollutant: No

Environmental Pollutant: Not Applicable

DOT-RQ: Yes DOT-RQ - Quantity: 10 lbs

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not Applicable

Special precautions

Department of Transportation (DOT):

Not Applicable

Road and Rail (ADR-RID):

Not Applicable

Air (IATA):

Not Applicable

Sea (IMDG):

Not Applicable

15. REGULATORY INFORMATION

USA - Federal regulations

TSCA - Toxic Substances Control Act

All the components are listed on the TSCA inventory

TSCA listed substances:

Print date 05/22/2025 Production Name ELASTOCOLOR PRIMER AR Page n. 7 of 10

titanium dioxide is listed in TSCA Section 8b polyethylene glycol is listed in TSCA Section 8b

monooleylether

free crystalline silica (Ø >10 μ) is listed in TSCA Section 8b carbendazim (ISO); methyl is listed in TSCA Section 8b

benzimidazol-2-ylcarbamate

SARA - Superfund Amendments and Reauthorization Act

Section 302 - Extremely Hazardous Substances:

No substances listed

Section 304 - Hazardous substances:

carbendazim (ISO); methyl benzimidazol-2-ylcarbamate

Section 313 - Toxic chemical list:

No substances listed

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act Substance(s) listed under CERCLA:

Substance(s) listed under CERCLA

carbendazim (ISO); methyl benzimidazol- Reportable quantity: 10 pounds

2-ylcarbamate

CAA - Clean Air Act

CAA listed substances:

No substances listed

CWA - Clean Water Act

CWA listed substances:

No substances listed

USA - State specific regulations

California Proposition 65

Substance(s) listed under California Proposition 65:

titanium dioxide Listed as carcinogen free crystalline silica (Ø >10 μ) Listed as carcinogen

Massachusetts Right to know

Substance(s) listed under Massachusetts Right to know:

titanium dioxide

free crystalline silica ($\emptyset > 10 \mu$)

Pennsylvania Right to know

Substance(s) listed under Pennsylvania Right to know:

titanium dioxide

free crystalline silica ($\emptyset > 10 \mu$)

New Jersey Right to know

Substance(s) listed under New Jersey Right to know:

titanium dioxide

free crystalline silica ($\emptyset > 10 \mu$)

carbendazim (ISO); methyl benzimidazol-2-ylcarbamate

Canada - Federal regulations

DSL - Domestic Substances List

All the substances are listed in the DSL.

NDSL - Non Domestic Substances List

This product complies with NDSL inventory

NPRI - National Pollutant Release Inventory

NPRI (National Pollutant Release Inventory) - List of substances listed.

No substances listed

16. OTHER INFORMATION

Safety Data Sheet dated: 4/21/2025 - version 5

Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. The information herein is presented in good faith and believed to

Print date 05/22/2025 Production Name ELASTOCOLOR PRIMER AR Page n. 8 of 10

be accurate as of the effective date given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or provincial, and local laws.

This document was prepared by a competent person who has received appropriate training.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Description

Code

| H315 | Causes skin irritation. | | | |
|---|---|--|--|--|
| H317 | May cause an allergic skin reaction. | | | |
| H340 | May cause genetic defects. | | | |
| H350 | May cause cancer. | | | |
| H351 | Suspected of causing cancer. | | | |
| H360FD | May damage fertility. May damage the unborn child. | | | |
| H372 | Causes damage to organs through prolonged or repeated exposure. | | | |
| H400 | Very toxic to aquatic life. | | | |
| H410 | Very toxic to aquatic life with long lasting effects. | | | |
| Code | Hazard class and hazard category | Description | | |
| A.2/2 | Skin Irrit. 2 | Skin irritation, Category 2 | | |
| A.4.2/1 | Skin Sens. 1 | Skin Sensitization, Category 1 | | |
| A.5/1B | Muta. 1B | Germ cell mutagenicity, Category 1B | | |
| A.6/1A | Carc. 1A | Carcinogenicity, Category 1A | | |
| A.6/2 | Carc. 2 | Carcinogenicity, Category 2 | | |
| A.7/1B | Repr. 1B | Reproductive toxicity, Category 1B | | |
| A.9/1 | STOT RE 1 | Specific target organ toxicity following repeated exposure, Category 1 | | |
| US-HAE/A1 | Aquatic Acute 1 | Acute aquatic hazard, category 1 | | |
| US-HAE/C1 | Aquatic Chronic 1 | Chronic (long term) aquatic hazard, category 1 | | |
| Logand to abbreviations and agreenyms used in the safety data sheet | | | | |

Legend to abbreviations and acronyms used in the safety data sheet:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

IMDG: International Maritime Code for Dangerous Goods.

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

CLP: Classification, Labeling, Packaging.

EINECS: European Inventory of Existing Commercial Chemical Substances.

INCI: International Nomenclature of Cosmetic Ingredients.

CAS: Chemical Abstracts Service (division of the American Chemical Society).

GefStoffVO: Ordinance on Hazardous Substances, Germany.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

DNEL: Derived No Effect Level.

PNEC: Predicted No Effect Concentration.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

STEL: Short Term Exposure limit.
STOT: Specific Target Organ Toxicity.
WGK: German Water Hazard Class.

KSt: Explosion coefficient.

Paragraphs modified from the previous revision:

- 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING
- 2. HAZARDS IDENTIFICATION
- 3. COMPOSITION/INFORMATION ON INGREDIENTS
- 4. FIRST AID MEASURES
- 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
- 9. PHYSICAL AND CHEMICAL PROPERTIES
- 11. TOXICOLOGICAL INFORMATION
- 12. ECOLOGICAL INFORMATION

Print date 05/22/2025 Production Name ELASTOCOLOR PRIMER AR Page n. 9 of 10

- 15. REGULATORY INFORMATION
- 16. OTHER INFORMATION

Print date 05/22/2025 Production Name ELASTOCOLOR PRIMER AR Page n. 10of 10