# Safety Data Sheet EPOJET / B

Safety Data Sheet dated: 01/22/2025 - version 8

Date of first edition: 05/30/2015

# **MAPEI**

#### 1. IDENTIFICATION

#### **Product identifier**

Mixture identification:

Trade name: EPOJET / B Trade code: 9015612

Recommended use of the chemical and restrictions on use

Recommended use: Hardener for epoxy products

Restrictions on use: Not available

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Company: MAPEI CORP. (USA and Puerto Rico)

1144 East Newport Center Drive - 33442 - Deerfield Beach - FL - USA

Phone: 954-246-8888

Responsable: RDProductSafety@mapei.com

**Emergency 24 hour numbers:** 

Emergency Number (USA/Canada) CHEMTREC 1(800) 424-9300 / 1(703) 527-3887

Emergency Transport CANUTEC (Canada) 1-613-996-6666

## 2. HAZARD(S) IDENTIFICATION







## Classification of the chemical

Acute toxicity (oral), Category 4 Harmful if swallowed.

Serious eye damage, Category 1 Causes serious eye damage.

Skin Sensitization, Category 1 May cause an allergic skin reaction.

Reproductive toxicity, Category 2 Suspected of damaging fertility. Suspected of damaging the unborn

child.

Specific target organ toxicity following repeated exposure,

Category 1

Causes damage to organs through prolonged or repeated exposure if

inhaled, in contact with skin and if swallowed.

Chronic (long term) aquatic hazard, category 3

Skin corrosion, Category 1C

Harmful to aquatic life with long lasting effects. Causes severe skin burns and eye damage.

## Label elements

## Hazard pictograms and Signal Word



Danger

#### **Hazard statements**

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure if inhaled, in contact with skin and if

swallowed.

H412 Harmful to aquatic life with long lasting effects.

## **Precautionary statements**

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe mist/vapours/spray.

Print date 01/22/2025 Production Name EPOJET / B Page n. 1 of 13

P270	Do not eat, drink or smoke when using this product.		
P273	Avoid release to the environment.		
P280	Wear protective gloves/clothing and eye/face protection.		
P301+P312	IF SWALLOWED: Call a doctor if you feel unwell.		
P301+P330+P33 1	IF SWALLOWED: rinse mouth. Do NOT induce vomiting.		
P302+P352	IF ON SKIN: Wash with plenty of water.		
P303+P361+P35 3	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.		
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.		
P305+P351+P33 8	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.		
P308+P313	IF exposed or concerned: Get medical advice/attention.		
P310	Immediately call a doctor.		
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.		
P363	Wash contaminated clothing before reuse.		
P501	Dispose of contents/container in accordance with applicable regulations.		
Ingredient(s) with unknown acute toxicity:			

None

## Hazards not otherwise classified identified during the classification process:

Wash skin thoroughly after handling.

None

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

## **Substances**

Not Relevant

## **Mixtures**

P264

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

## List of components

Qty	Name	Ident. Numb.	Classification
50-75 %	polyamido amine; Fatty acids, tall-oil, reaction products with tetraethylenepentamine	CAS:68953-36-6 EC:273-201-6	Skin Corr. 1C, H314; Eye Dam. 1, H318; Skin Sens. 1, H317
10-20 %	3,6-diazaoctanethylenediamin; triethylenetetramine	CAS:112-24-3 EC:203-950-6 Index:612-059-00-5	Skin Corr. 1B, H314; Skin Sens. 1, H317; Aquatic Chronic 3, H412; Acute Tox. 4, H312
10-20 %	benzyl alcohol	CAS:100-51-6 EC:202-859-9 Index:603-057-00-5	Acute Tox. 4, H302; Eye Irrit. 2A, H319
10-20 %	2-piperazin-1-ylethylamine	CAS:140-31-8 EC:205-411-0 Index:612-105-00-4	Acute Tox. 3, H311; Repr. 2, H361; STOT RE 1, H372; Acute Tox. 4, H302; Skin Corr. 1B, H314; Skin Sens. 1, H317; Aquatic Chronic 3, H412
5-10 %	2,4,6-tris(dimethylaminomethyl)phenol	CAS:90-72-2 EC:202-013-9 Index:603-069-00-0	Skin Corr. 1C, H314; Eye Dam. 1, H318; Acute Tox. 4, H302
2.5-5 %	3,6,9-triazaundecamethylenediamine tetraethylenepentamine	CAS:112-57-2 EC:203-986-2 Index:612-060-00-0	Skin Corr. 1B, H314; Skin Sens. 1, H317; Aquatic Chronic 2, H411; Acute Tox. 4, H302; Acute Tox. 4, H312
1-2.5 %	bis[(dimethylamino)methyl]phenol	CAS:71074-89-0 EC:275-162-0	Skin Corr. 1C, H314
0.1-0.25 %	2,2'-iminodi(ethylamine)	CAS:111-40-0 EC:203-865-4 Index:612-058-00-X	Acute Tox. 2, H330; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Corr. 1B, H314; STOT SE 3, H335; Skin Sens. 1, H317

Print date 01/22/2025 Production Name EPOJET / B Page n. 2 of 13

#### 4. FIRST AID MEASURES

#### Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

OBTAIN IMMEDIATE MEDICAL ATTENTION.

Obtain medical attention if skin related symptoms persist.

Remove contaminated clothing immediately and dispose of safely.

After contact with skin, wash immediately with soap and plenty of water.

#### In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an opthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Give nothing to eat or drink.

In case of Inhalation:

If breathing is irregular or stopped, administer artificial respiration.

In case of inhalation, consult a doctor immediately and show him packing or label.

#### Most important symptoms/effects, acute and delayed

Eye irritation

Eye damages

Skin Irritation

Erythema

## Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

(see paragraph 4.1)

## **5. FIRE-FIGHTING MEASURES**

## **Extinguishing media**

Suitable extinguishing media:

Water.

Carbon dioxide (CO2).

## Unsuitable extinguishing media:

None in particular.

## Specific hazards arising from the chemical

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products: Not available

Explosive properties: Not available Oxidizing properties: Not available

## Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

## **6. ACCIDENTAL RELEASE MEASURES**

## Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Limit leakages with earth or sand.

## Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand  $% \left( 1\right) =\left( 1\right) \left( 1\right)$ 

Retain contaminated washing water and dispose it.

## 7. HANDLING AND STORAGE

## Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Print date 01/22/2025 Production Name EPOJET / B Page n. 3 of 13

Exercise the greatest care when handling or opening the container.

Use localized ventilation system.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

## Conditions for safe storage, including any incompatibilities

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

Storage temperature: Not available

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## **Control parameters**

#### **Community Occupational Exposure Limits (OEL)**

	OEL Type	Country	Occupational Exposure Limit
benzyl alcohol CAS: 100-51-6	MAK	GERMANY	Long Term: 22 mg/m3 - 5 ppm
	MAK	SWITZERLAN D	Long Term: 22 mg/m3 - 5 ppm
2,2'-iminodi(ethylamine) CAS: 111-40-0	ACGIH		Long Term: 1 ppm Skin - URT and eye irr
	ACGIH		Long Term: 1 ppm Skin - potential significant contribution to overall exposure by the cutaneous route; eye and upper respiratory tract irritation
	MAK	AUSTRIA	Long Term: 4 mg/m3 - 1 ppm
	MAK	SWITZERLAN D	Long Term: 4 mg/m3 - 1 ppm

## **Predicted No Effect Concentration (PNEC) values**

2-piperazin-1- Exposure Route: Fresh Water; PNEC Limit: 0.058 mg/l

ylethylamine CAS: 140-31-8

Exposure Route: Marine water; PNEC Limit: 0.0058 mg/l
Exposure Route: Intermittent release; PNEC Limit: 0.58 mg/l
Exposure Route: Freshwater sediments; PNEC Limit: 215 mg/kg
Exposure Route: Marine water sediments; PNEC Limit: 21.5 mg/kg

Exposure Route: Soil; PNEC Limit: 42.9 mg/kg

Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 250 mg/l

3,6,9- Exposure Route: Fresh Water; PNEC Limit: 0.00068 mg/l

triazaundecamethylenedia

mine

tetraethylenepentamine

CAS: 112-57-2

Exposure Route: Marine water; PNEC Limit: 0.00068 mg/l

Exposure Route: Freshwater sediments; PNEC Limit: 3.34 mg/kg Exposure Route: Marine water sediments; PNEC Limit: 0.343 mg/kg

Exposure Route: Soil; PNEC Limit: 0.683 mg/kg

2,2'-iminodi(ethylamine) Exposure Route: Fresh Water; PNEC Limit: 0.56 mg/l

CAS: 111-40-0

Exposure Route: Marine water; PNEC Limit: 0.056 mg/l

Exposure Route: Freshwater sediments; PNEC Limit: 1072 mg/kg Exposure Route: Marine water sediments; PNEC Limit: 107.2 mg/kg

Exposure Route: Intermittent release; PNEC Limit: 0.32 mg/l

Print date 01/22/2025 Production Name EPOJET / B Page n. 4 of 13

Exposure Route: Microorganisms in sewage treatments; PNEC Limit: 6 mg/l

Exposure Route: Soil; PNEC Limit: 214 mg/kg

#### **Derived No Effect Level (DNEL) values**

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects

diazaoctanethylenediamin Worker Industry: 5380 mg/m3; Consumer: 1600 mg/m3

triethylenetetramine CAS: 112-24-3

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects

Worker Industry: 0.57 mg/kg

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects

Worker Industry: 1 mg/m3; Consumer: 0.29 mg/m3

Exposure Route: Human Dermal; Exposure Frequency: Long Term, local effects

Worker Industry: 0.028 mg/m3; Consumer: 0.43 mg/cm2

Exposure Route: Human Dermal; Exposure Frequency: Short Term, systemic effects

Consumer: 8 mg/kg

Exposure Route: Human Oral; Exposure Frequency: Short Term, systemic effects

Consumer: 20 mg/kg

Exposure Route: Human Dermal: Exposure Frequency: Short Term, local effects

Consumer: 1 mg/cm2

Exposure Route: Human Oral; Exposure Frequency: Long Term, local effects

Consumer: 0.43 mg/cm2

2-piperazin-1-Exposure Route: Human Dermal; Exposure Frequency: Short Term, systemic effects

ylethylamine Worker Industry: 20 mg/kg; Consumer: 10 mg/kg CAS: 140-31-8

Exposure Route: Human Dermal; Exposure Frequency: Short Term, local effects

Worker Industry: 0.04 mg/cm2; Consumer: 0.02 mg/cm2

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects

Worker Industry: 3.3 mg/kg; Consumer: 1.7 mg/kg

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects

Worker Industry: 3.6 mg/m3; Consumer: 0.9 mg/m3

Exposure Route: Human Dermal; Exposure Frequency: Long Term, local effects

Worker Industry: 0.006 mg/cm2; Consumer: 0.003 mg/cm2

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects

Worker Industry: 21.4 mg/m3; Consumer: 5.3 mg/m3

Exposure Route: Human Oral; Exposure Frequency: Short Term, systemic effects

Consumer: 1.5 mg/kg

Exposure Route: Human Oral; Exposure Frequency: Long Term, systemic effects

Consumer: 0.3 mg/kg

2,4,6-Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects tris

Worker Industry: 0.31 mg/m3

(dimethylaminomethyl)

phenol

CAS: 90-72-2

3,6,9-Exposure Route: Human Dermal; Exposure Frequency: Short Term, systemic effects

triazaundecamethylenedia Consumer: 10 mg/kg

mine

tetraethylenepentamine

CAS: 112-57-2

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects

Worker Professional: 0.74 mg/kg

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects

Consumer: 0.32 mg/kg

Exposure Route: Human Oral; Exposure Frequency: Long Term, systemic effects

Consumer: 0.53 mg/kg

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects

Worker Professional: 0.00129 mg/l

01/22/2025 Production Name EPOJET / B Print date Page n. 5 of 13 Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects

Consumer: 0.00038 mg/l

2,2'-iminodi(ethylamine)

CAS: 111-40-0

Exposure Route: Human Oral; Exposure Frequency: Short Term, local effects

Consumer: 4.88 mg/kg

Exposure Route: Human Inhalation; Exposure Frequency: Short Term, systemic effects

Worker Industry: 92.1 mg/m3; Consumer: 27.5 mg/m3

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, systemic effects

Worker Industry: 15.4 mg/m3; Consumer: 4.6 mg/m3

Exposure Route: Human Inhalation; Exposure Frequency: Long Term, local effects

Worker Industry: 2.6 mg/m3

Exposure Route: Human Dermal; Exposure Frequency: Long Term, systemic effects

Worker Industry: 11.4 mg/kg; Consumer: 4.88 mg/kg

Appropriate engineering controls: Not available

## **Individual protection measures**

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Suitable materials for safety gloves; 29 CFR 1910.138 - ANSI/ISEA 105: Polychloroprene - CR: thickness >=0,5mm; breakthrough time >=480min. Nitrile rubber - NBR: thickness >=0,35mm; breakthrough time >=480min. Butyl rubber - IIR: thickness >=0,5mm; breakthrough time >=480min.

Fluorinated rubber - FKM: thickness >=0,4mm; breakthrough time >=480min.

Use impervious gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

#### Respiratory protection:

Respiratory protection must be used where exposure levels exceed workplace exposure limits. Refer to 29 CFR 1910.134 - CSA Z94.4 for information on selection and use of appropriate respiratory protection equipment.

Use adequate protective respiratory equipment.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

## Information on basic physical and chemical properties

Physical state: Liquid

Appearance and colour: Viscous Amber

Odour: No data available

Odour threshold: No data available

pH: No data available

Melting point / freezing point: No data available Initial boiling point and boiling range: 200 °C (392 °F)

Flash point: 100 °C (212 °F) Evaporation rate: No data available

Upper/lower flammability or explosive limits: No data available

Vapour density: No data available Vapour pressure: No data available Relative density: 0.99 g/cm3 Solubility in water: No data available

Solubility in water: No data available Solubility in oil: No data available

Partition coefficient (n-octanol/water): No data available

Auto-ignition temperature: No data available Decomposition temperature: No data available

Viscosity: No data available

Explosive properties: No data available Oxidizing properties: No data available Solid/gas flammability: No data available

## Other information

Substance Groups relevant properties No data available

Miscibility: No data available
Fat Solubility: No data available
Conductivity: No data available

Print date 01/22/2025 Production Name EPOJET / B Page n. 6 of 13

#### 10. STABILITY AND REACTIVITY

#### Reactivity

Stable under normal conditions

#### **Chemical stability**

Data not available.

## Possibility of hazardous reactions

None.

#### **Conditions to avoid**

Stable under normal conditions.

#### **Incompatible materials**

None in particular.

#### **Hazardous decomposition products**

None.

## 11. TOXICOLOGICAL INFORMATION

## Information on toxicological effects

#### **Toxicological Information of the Preparation**

a) acute toxicity The product is classified: Acute toxicity (oral), Category 4(H302)

ATEmix - Oral: 1966.1 mg/kg bw

b) skin corrosion/irritation
 c) serious eye damage/irritation
 d) respiratory or skin sensitisation
 The product is classified: Serious eye damage, Category 1(H318)
 The product is classified: Skin Sensitization, Category 1(H317)

e) germ cell mutagenicity Not classified

Based on available data, the classification criteria are not met

f) carcinogenicity Not classified

Based on available data, the classification criteria are not met

g) reproductive toxicity The product is classified: Reproductive toxicity, Category 2(H361)

h) STOT-single exposure Not classified

Based on available data, the classification criteria are not met

i) STOT-repeated exposure The product is classified: Specific target organ toxicity following repeated exposure,

Category 1(H372)

j) aspiration hazard Not classified

Based on available data, the classification criteria are not met

## Toxicological information on main components of the mixture:

3,6- a) acute toxicity LD50 Skin Rabbit 1465 mg/kg

diazaoctanethylenediamin; triethylenetetramine

LD50 Oral Rat = 2500 mg/kg

benzyl alcohol a) acute toxicity LD50 Oral Rat = 1620 mg/kg

2-piperazin-1- a) acute toxicity LD50 Skin Rabbit = 866 mg/kg ylethylamine

LD50 Oral Rabbit > 2097 mg/kg LD50 Skin Rabbit = 880  $\mu$ L/kg LD50 Oral Rat = 2140  $\mu$ L/kg

e) germ cell mutagenicity NOAEL Rat > 899 mg/kgg) reproductive toxicity NOAEL Oral Rat = mg/kg

2,4,6- a) acute toxicity LD50 Oral Rat = 2169 mg/kg tris

(dimethylaminomethyl) phenol

LD50 Skin Rat > 1 ml/kg

Print date 01/22/2025 Production Name EPOJET / B Page n. 7 of 13

LD50 Skin Rabbit = 1045 mg/kg LD50 Oral Rat = 1553 mg/kg LC50 Inhalation Mist 0.07 mg/l

## Substance(s) listed on the IARC Monographs:

None

Substance(s) listed as OSHA Carcinogen(s):

None

Substance(s) listed as NIOSH Carcinogen(s):

None

Substance(s) listed on the NTP report on Carcinogens:

None

## 12. ECOLOGICAL INFORMATION

## **Toxicity**

Adopt good working practices, so that the product is not released into the environment. Eco-Toxicological Information:

## List of Eco-Toxicological properties of the product

The product is classified: Chronic (long term) aquatic hazard, category 3(H412)

•			, ,
List of Eco-Toxicological properties of the components			
Component	Ident. Numb.	Ecotox Data	
3,6-diazaoctanethylenediamin; triethylenetetramine	CAS: 112-24-3 - EINECS: 203- 950-6 - INDEX: 612-059-00-5	a) Aquatic acute toxicity : IUCLID	LC50 Fish Poecilia reticulata = 570 mg/L 96h
		a) Aquatic acute toxicity : IUCLID	LC50 Fish Pimephales promelas = 495 mg/L 96h
		a) Aquatic acute toxicity: IUCLID	EC50 Daphnia Daphnia magna = 31.1 mg/L 48h
		a) Aquatic acute toxicity: 72h IUCLID	EC50 Algae Desmodesmus subspicatus = 2.5 mg/L
		a) Aquatic acute toxicity : mg/L 72h IUCLID	EC50 Algae Pseudokirchneriella subcapitata = 20
		a) Aquatic acute toxicity : mg/L 96h EPA	EC50 Algae Pseudokirchneriella subcapitata = 3.7
benzyl alcohol	CAS: 100-51-6 - EINECS: 202- 859-9 - INDEX: 603-057-00-5	a) Aquatic acute toxicity : EPA	LC50 Fish Pimephales promelas = 460 mg/L 96h
2-piperazin-1-ylethylamine	CAS: 140-31-8 - EINECS: 205- 411-0 - INDEX: 612-105-00-4	a) Aquatic acute toxicity:	LC50 Fish = 2190 mg/L 96
		a) Aquatic acute toxicity:	EC50 Daphnia = 58 mg/L 48
		a) Aquatic acute toxicity:	EC50 Algae > 1000 mg/L 72
		a) Aquatic acute toxicity:	LC50 Fish Pimephales promelas 1950 mg/L 96h EPA
		a) Aquatic acute toxicity : IUCLID	LC50 Fish Poecilia reticulata > 1000 mg/L 96h
		a) Aquatic acute toxicity : IUCLID	LC50 Fish Oncorhynchus mykiss >= 100 mg/L 96h
		a) Aquatic acute toxicity : IUCLID	EC50 Daphnia Daphnia magna = 32 mg/L 48h
		a) Aquatic acute toxicity : mg/L 72h IUCLID	EC50 Algae Pseudokirchneriella subcapitata = 495

Print date 01/22/2025 Production Name EPOJET / B Page n. 8 of 13

2,4,6- CAS: 90-72-2 - a) Aquatic acute toxicity: LC50 Fish = 175 mg/L 96h

tris(dimethylaminomethyl)phenol EINECS: 202-

013-9 - INDEX: 603-069-00-0

612-060-00-0

a) Aquatic acute toxicity: EC50 Algae = 46.7 mg/L 72ha) Aquatic acute toxicity: NOEC Algae = 25.1 mg/L 72h

3,6,9- CAS: 112-57-2 - a) Aquatic acute toxicity: LC50 Fish Poecilia reticulata = 420 mg/L 96h

3,6,9- CAS: 112-5/-2 - a) Aquatic acute toxicity: LC50 Fish Poecilia reticulata = 420 mg/L 96h triazzundecamethylanediamine FINECS: 203- TUCLID

triazaundecamethylenediamine EINECS: 203- IUCLID tetraethylenepentamine 986-2 - INDEX:

a) Aquatic acute toxicity: EC50 Daphnia Daphnia magna = 24.1 mg/L 48h

 a) Aquatic acute toxicity: EC50 Algae Pseudokirchneriella subcapitata = 2.1 mg/L 72h IUCLID

2,2'-iminodi(ethylamine) CAS: 111-40-0 - a) Aquatic acute toxicity: LC50 Fish = 430 mg/L 96

**TUCL ID** 

EINECS: 203-865-4 - INDEX: 612-058-00-X

a) Aquatic acute toxicity: EC50 Daphnia = 32 mg/L 48

#### Persistence and degradability

N.A.

#### **Bioaccumulative potential**

N.A.

## Mobility in soil

N.A.

#### Other adverse effects

N.A.

#### 13. DISPOSAL CONSIDERATIONS

#### **Waste treatment methods**

The generation of waste should be avoided or minimized wherever possible. Recover if possible.

## Methods of disposal:

Disposal of this product, solutions, packaging and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor.

Do not dispose of waste into sewers.

## Disposal considerations:

Do not allow to enter drains or watercourses.

Dispose of product according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions. For further information, contact your local waste authority.

#### Special precautions:

This material and its container must be disposed of in a safe way. Care should be taken when handling untreated empty containers. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Empty containers or liners may retain some product residues. Do not re-use empty containers.

## 14. TRANSPORT INFORMATION

## **UN** number

DOT-UN Number: UN1760 ADR-UN number: 1760 IATA-Un number: 1760 IMDG-Un number: 1760

## UN proper shipping name

DOT-Proper Shipping Name: Corrosive liquids, n.o.s. (polyamides - triethylenetetramine) ADR-Shipping Name: CORROSIVE LIQUID, N.O.S. (polyamides - triethylenetetramine) IATA-Technical name: CORROSIVE LIQUID, N.O.S. (polyamides - triethylenetetramine) IMDG-Technical name: CORROSIVE LIQUID, N.O.S. (polyamides - triethylenetetramine)

Print date 01/22/2025 Production Name EPOJET / B Page n. 9 of 13

Transport hazard class(es)

DOT-Hazard Class: 8

ADR-Class: 8
IATA-Class: 8
IMDG-Class: 8

**Packing group** 

DOT Packing Group: III ADR-Packing Group: III IATA-Packing group: III IMDG-Packing group: III

**Environmental hazards** 

Marine pollutant: No

Environmental Pollutant: Not Applicable

DOT-RQ: No

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not Applicable

**Special precautions** 

Department of Transportation (DOT):

DOT-Special Provision(s): IB3, T7, TP1, TP28

DOT-Label(s): 8

DOT-Symbol: N/A

DOT-Cargo Aircraft: N/A

DOT-Passenger Aircraft: N/A

DOT-Bulk: N/A DOT-Non-Bulk: N/A

DOT-Limited Quantity threshold: 5 L

Road and Rail (ADR-RID):

ADR exempt: No ADR-Label: 8

ADR-Hazard identification number: 80

ADR-Transport category (Tunnel restriction code): 3 (E)

Air (IATA):

IATA-Passenger Aircraft: 852 IATA-Cargo Aircraft: 856

IATA-Label: 8

 $IATA\hbox{-}Subsidiary\ hazards:\ \hbox{-}$ 

IATA-Erg: 8L

IATA-Special Provisions: A3 A803

Sea (IMDG):

IMDG-Stowage Code: Category A SW2

IMDG-Stowage Note: IMDG-Subsidiary hazards: -

IMDG-Special Provisions: 223 274

IMDG-EMS: F-A, S-B

## 15. REGULATORY INFORMATION

## **USA - Federal regulations**

**TSCA - Toxic Substances Control Act** 

All the components are listed on the TSCA inventory

**TSCA listed substances:** 

polyamido amine; Fatty acids, tall- is listed in TSCA Section 8b oil, reaction products with tetraethylenepentamine

3,6-diazaoctanethylenediamin;

triethylenetetramine

is listed in TSCA Section 8b

benzyl alcohol is listed in TSCA Section 8b

Print date 01/22/2025 Production Name EPOJET / B Page n. 10of 13

2-piperazin-1-ylethylamine is listed in TSCA Section 8b 2,4,6- is listed in TSCA Section 8b

tris(dimethylaminomethyl)phenol

3,6,9- is listed in TSCA Section 8b

triazaundecamethylenediamine tetraethylenepentamine

2,2'-iminodi(ethylamine) is listed in TSCA Section 8b

## **SARA - Superfund Amendments and Reauthorization Act**

## **Section 302 - Extremely Hazardous Substances:**

No substances listed

#### Section 304 - Hazardous substances:

No substances listed

#### Section 313 - Toxic chemical list:

No substances listed

## CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act Substance(s) listed under CERCLA:

No substances listed

#### **CAA - Clean Air Act**

## **CAA listed substances:**

benzyl alcohol is listed in CAA Section 112(b) - HON 3,6,9- is listed in CAA Section 112(b) - HON

triazaundecamethylenediamine tetraethylenepentamine

#### **CWA - Clean Water Act**

#### **CWA listed substances:**

No substances listed

## **USA - State specific regulations**

#### **California Proposition 65**

## Substance(s) listed under California Proposition 65:

No substances listed

#### Massachusetts Right to know

## Substance(s) listed under Massachusetts Right to know:

 ${\it 3,6-diazaoctanethylenediamin;}\ triethylenete tramine$ 

benzyl alcohol

2-piperazin-1-ylethylamine

 $3,6,9\hbox{-triaz} a undecame thy lene diamine\ tetra ethylene pentamine$ 

2,2'-iminodi(ethylamine)

## Pennsylvania Right to know

## Substance(s) listed under Pennsylvania Right to know:

3,6-diazaoctanethylenediamin; triethylenetetramine

benzyl alcohol

2-piperazin-1-ylethylamine

3,6,9-triazaundecamethylenediamine tetraethylenepentamine

2,2'-iminodi(ethylamine)

#### New Jersey Right to know

## Substance(s) listed under New Jersey Right to know:

3,6-diazaoctanethylenediamin; triethylenetetramine

2-piperazin-1-ylethylamine

3,6,9-triazaundecamethylenediamine tetraethylenepentamine

2,2'-iminodi(ethylamine)

## Canada - Federal regulations

#### **DSL - Domestic Substances List**

All the substances are listed in the DSL.

## NDSL - Non Domestic Substances List

This product complies with NDSL inventory

Print date 01/22/2025 Production Name EPOJET / B Page n. 11of 13

No substances listed

#### 16. OTHER INFORMATION

Safety Data Sheet dated: 1/22/2025 - version 8

Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. The information herein is presented in good faith and believed to be accurate as of the effective date given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or provincial, and local laws.

This document was prepared by a competent person who has received appropriate training.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Code	Description		
H302	Harmful if swallowed.		
H311	Toxic in contact with skin.		
H312	Harmful in contact with skin.		
H314	Causes severe skin burns and eye damage.		
H317	May cause an allergic skin reaction.		
H318	Causes serious eye damage.		
H319	Causes serious eye irritation.		
H330	Fatal if inhaled.		
H335	May cause respiratory irritation.		
H361	Suspected of damaging fertility or the unborn child.		
H372	Causes damage to organs through prolonged or repeated exposure if inhaled.		
H411	Toxic to aquatic life with long lasting effects.		
H412	Harmful to aquatic life with long lasting effects.		
Code	Hazard class and hazard category Description		

Code	Hazard class and hazard category	Description
A.1/2/Inhal	Acute Tox. 2	Acute toxicity (inhalation), Category 2
A.1/3/Dermal	Acute Tox. 3	Acute toxicity (dermal), Category 3
A.1/4/Dermal	Acute Tox. 4	Acute toxicity (dermal), Category 4
A.1/4/Oral	Acute Tox. 4	Acute toxicity (oral), Category 4
A.2/1B	Skin Corr. 1B	Skin corrosion, Category 1B
A.2/1C	Skin Corr. 1C	Skin corrosion, Category 1C
A.3/1	Eye Dam. 1	Serious eye damage, Category 1
A.3/2A	Eye Irrit. 2A	Eye irritation, Category 2A
A.4.2/1	Skin Sens. 1	Skin Sensitization, Category 1
A.7/2	Repr. 2	Reproductive toxicity, Category 2
A.8/3	STOT SE 3	Specific target organ toxicity following single exposure, Category 3
A.9/1	STOT RE 1	Specific target organ toxicity following repeated exposure, Category 1
US-HAE/C2	Aquatic Chronic 2	Chronic (long term) aquatic hazard, category 2
US-HAE/C3	Aquatic Chronic 3	Chronic (long term) aquatic hazard, category 3

## Legend to abbreviations and acronyms used in the safety data sheet:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

IMDG: International Maritime Code for Dangerous Goods.

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

CLP: Classification, Labeling, Packaging.

EINECS: European Inventory of Existing Commercial Chemical Substances.

INCI: International Nomenclature of Cosmetic Ingredients.

CAS: Chemical Abstracts Service (division of the American Chemical Society).

Print date 01/22/2025 Production Name EPOJET / B Page n. 12of 13

GefStoffVO: Ordinance on Hazardous Substances, Germany.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

DNEL: Derived No Effect Level.

PNEC: Predicted No Effect Concentration.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

STEL: Short Term Exposure limit. STOT: Specific Target Organ Toxicity. WGK: German Water Hazard Class.

KSt: Explosion coefficient.

## Paragraphs modified from the previous revision:

- 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING
- 2. HAZARDS IDENTIFICATION
- 3. COMPOSITION/INFORMATION ON INGREDIENTS
- 4. FIRST AID MEASURES
- 6. ACCIDENTAL RELEASE MEASURES
- 7. HANDLING AND STORAGE
- 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
- 9. PHYSICAL AND CHEMICAL PROPERTIES
- 11. TOXICOLOGICAL INFORMATION
- 12. ECOLOGICAL INFORMATION
- 14. TRANSPORT INFORMATION
- 15. REGULATORY INFORMATION
- 16. OTHER INFORMATION

Print date 01/22/2025 Production Name EPOJET / B Page n. 13of 13